

computar®

2014.03



C C T V
L E N S
P R O D U C T
G U I D E

14-15



40
JAPANESE ENGINEERING
YEARS



The World Standard for Industrial Lenses.

At CBC, we have set the world standard for industrial lenses through the design, manufacture and global sales of the "Computar" brand. Since the very beginning of the video security market, we have established a strong worldwide distribution network. As a pioneer in CCTV lenses, CBC and the Computar brand have grown along with the demands of the world market.

Computar CCTV lenses were introduced in the U.S.A. during the mid 1970s and have continued to meet security challenges globally for more than 30 years. Today, we lead the industry in Japan, Europe, Asia and markets all over the world. We offer a comprehensive lineup of high-quality products with excellent cost performance. Our designs utilize leading-edge technology, enabling us to achieve the highest quality while also ramping up production in our factories in Japan and abroad. We are proud to have an established worldwide sales network, built on the excellence of our Computar products.

CBC is committed to maintaining the world standard for industrial lenses through continuous research and development. We continue to strive to achieve even greater quality to meet our customer needs for today's evolving security challenges.

CONTENTS

01	FEATURE INDICATION		FEATURE INDICATION
02	MODEL NAME CODING RULE		MODEL NAME CODING RULE
07	MANUAL IRIS	C-MOUNT / CS-MOUNT	MANUAL IRIS
08	AUTO IRIS	DC DRIVE / VIDEO DRIVE	AUTO IRIS
10	VARI-FOCAL MANUAL IRIS		VARI-FOCAL MANUAL IRIS
13	VARI-FOCAL AUTO IRIS	DC DRIVE	VARI-FOCAL AUTO IRIS
16	VARI-FOCAL AUTO IRIS	VIDEO DRIVE	VARI-FOCAL AUTO IRIS
19	PINHOLE / MANUAL ZOOM	MANUAL IRIS / DC DRIVE / VIDEO DRIVE	PINHOLE MANUAL ZOOM
21	MOTORIZED ZOOM	1/3"	MOTORIZED ZOOM
25	MOTORIZED ZOOM	1/2" 1/1.8" MEGAPIXEL	MOTORIZED ZOOM
37	MEGAPIXEL	SECURITY / FA • IMAGE PROCESSING	MEGAPIXEL
49	ACCESSORIES		ACCESSORIES THERMAL
50	THERMAL		ACCESSORIES THERMAL
51	TECHNICAL INFORMATION		TECHNICAL INFORMATION
61	ANGLE OF VIEW		ANGLE OF VIEW



FEATURE INDICATION

Lens type

FIX	Fixed Focal	Fixed focal length, very simple and compact design
VARI	Vari-Focal	Compact design, focal length adjusted manually
ZOOM	Zoom	Focal length adjusted without focus shift of image plane

Iris type

MANUAL	Manual Iris	Manually operated iris
DC	DC Auto Iris	Auto iris supporting DC controlled cameras
VIDEO	Video Auto Iris	Auto iris supporting Video controlled cameras
P-iris	P-iris	Auto iris supporting P-iris controlled cameras
3 MOTOR	3 Motors	Operated iris, zoom and focus by electric remote control

Function

F1.0	Wide Aperture Ratio	Large aperture that transmits more light
ASP	Aspherical Lens	Aspherical lens which greatly improves the image quality and compact design
1MP	Megapixel Lens	High definition lens which is used mainly with 1MP cameras
2MP	Megapixel Lens	High definition lens which is used mainly with 2MP cameras
3MP	Megapixel Lens	High definition lens which is used mainly with 3MP cameras
5MP	Megapixel Lens	High definition lens which is used mainly with 5MP cameras
IR	Day & Night	Lens optimized for both visible and new IR spectrum which eliminates focus shift with Day&Night cameras

Feature of Focal Length

WIDE	Wide Angle Lens	Lens provides a wide field of view
TELE	Telephoto Lens	Lens provides a small field of view or magnified image in long range applications

Feature of Zoom

SPOT FILTER	Spot Filter	A neutral density filter inside the lens that attenuates the amount of light transmission from very bright object
PRESET	Preset on Focus & Zoom	The model which has the function of preset on focus and zoom
OVERRIDE	Override Manual	The model which enables manual control from remote locations

Application of Megapixel / FA Lens

SECURITY	Security	For Security, available for monitoring at infinity. Provides good image recognition accuracy
FA	FA-Image Processing	For Factory Automation or Image Processing, used in monitoring at a close proximity

Thermal

Athermal	Athermal	Athermalized lens which maintains focus position over wide change of the environmental temperature
17µm	17µm pitch Sensor	Thermal lens which can be used with 17µm pitch sensor

MODEL NAME CODING RULE

Manual Iris / Auto Iris (DC&Video) / Vari-Focal Manual Iris / Vari-Focal Auto Iris (DC & Video)

T2314FICS	T		23	14		FI	CS	
T3Z2910CS	T		3Z	29	10		CS	
HG3Z4512AFCS-IR	H	G	3Z	45	12	AF	CS	-IR
HG2Z0414FC-MP	H	G	2Z	04	14	F	C	-MP
AG3Z3112KCS-MPIR	A	G	3Z	31	12	K	CS	-MPIR
	①	②	③	④	⑤	⑥	⑦	⑧

① Sensor Size	T..... 1/3 inch
	A..... 1/2.7 inch
	H..... 1/2 inch
	E..... 1/1.8 inch
	M..... 2/3 inch
② With Galvanometer (Auto Iris)	
③ Zoom Ratio	HG2Z0414FC-MP... 2 times (f=4~8mm)
④ Focal Length	T2314FICS..... f=2.3 mm
⑤ Aperture	T3Z2910CS..... F1.0
⑥ Iris Type	FI / Blank..... Manual Iris
	AF..... Auto Iris (Video)
	F..... Auto Iris (DC)
	K..... P-iris
⑦ Mount Type	CS..... CS-Mount
	C..... C-Mount
⑧ Character	IR..... InfraRed Lens (Day & Night)
	MP..... Megapixel
	P..... Pinhole

Manual Zoom

H6Z0812	H		6Z	08	12			
T6Z5710AIDC-CS	T		6Z	57	10	AI	DC	-CS
H6Z0812AIVD	H		6Z	08	12	AI	VD	
	①		③	④	⑤	⑨	⑩	⑦

⑨ Auto Iris	
⑩ Iris Type	DC..... DC Drive
	VD..... Video Drive

Motorized Zoom

T21Z5816M-CS	T		21Z	58	16	M	-CS	
H10Z1218DC	H		10Z	12	18	DC		
H16Z7516AMSPR-IR	H		16Z	75	16	AMSPR	-IR	
H60Z1238A-IRF	H		60Z	12	38	A	-IR	F
	①		③	④	⑤	⑪	⑦	⑧

⑪ Functional Identification	M..... 3 Motors (Iris,Focus & Zoom by Motorized Control)
	MP..... 3 Motors + Preset
	MS..... 3 Motors + Spot Filter
	MSP..... 3 Motors + Spot Filter + Preset
	AMS..... Auto Iris (Video)+Spot Filter
	AMSP..... Auto Iris (Video)+Spot Filter + Preset
	AMSR..... Auto Iris (Video)+Spot Filter+ Over-Ride
	AMSPR..... Auto Iris (Video) +Spot Filter+ Preset + Over-Ride
	DC..... Auto Iris (DC)+Spot Filter
	PDC..... Auto Iris (DC)+Spot Filter+ Preset
	A..... Auto Iris (Video)+Spot Filter+Preset+Over-Ride+Lever Remote+ALC remote
	F..... Fog through Filter
	EX..... 2X extender

※ This rule does not apply to some products



Megapixel Vari-Focal lens series

- Designed for optimal performance with megapixel camera applications
- IR corrected optics
- Precise focus adjustment
- Covers a range of focal lengths from super wide to telephoto
- Provides a high contrast and a sharp picture
- Delivers clear images in low-light conditions
- Compact design
- Built-in slip mount mechanism
- Locking mechanism for zoom and focus rings
- Manual, DC and P-iris models are available

▶ See page 38, 39, 40



For 3MP/HDTV1080p network camera

This lens is designed to capture detailed images for security applications that require exceptional precision. High quality optics maximize performance with 3MP/HDTV1080p megapixel camera sensors and produce a sharp picture across the entire image plane, including the corners.

Precise focus adjustment

Setting the focus on megapixel IP cameras can be a challenge, especially when facing the limited adjustment ranges and transmission delays, that occur through a network. For this series, the focus mechanism has been designed to allow more precise focus control.

Manual, DC and P-iris models are available

Both manual iris and DC auto iris models are available to meet your needs. The P-iris lens, combined with specialized camera software, delivers superior picture quality, enhancing contrast, resolution and depth of field.


IR corrected optics designed for 24-hour surveillance

Megapixel cameras with retractable IR cut filters must use IR corrected lenses to avoid focus shift. Our lenses are designed to work with these true day & night cameras, maintaining sharp focus in both day and night modes, even in twilight.


Covering a range of focal lengths, from super wide to telephoto

The AG3Z3112 series allows you to capture 105.4-degree overview in a 16:9 format. Telephoto models in the AG4Z1214 series are suitable for various outdoor and high ceiling applications.

Megapixel lens



Non-Megapixel lens



Note: Images above are for illustration purposes only.

5 megapixel
7x macro zoom
Telecentric design



Megapixel zoom ratio: 0.5x - 0.07x

Telecentric design: 0.25x - 0.5x

Adjustable W.D: 182mm - 577.2mm

This high performance lens incorporates two design functions. It operates both as a 7x macro zoom lens with 0.07x to 0.5x magnification and as a telecentric lens within the 0.25X to 0.5x magnification range. It provides excellent brightness throughout the zoom range, maintaining 70% illumination even in the corners of the image. Working distance is adjustable from 182 - 577.2mm, and an F4.3-32C manual iris allows for precise depth of field and contrast adjustments. The lens is suitable for cameras up to 5 megapixel resolution for a 1.1-inch sensor. This combination of features offers the versatility to meet a wide range of industrial applications.

- **Zoom ratio: 7:1**
- **Sensor: 1.1 inch (diagonal 17.4mm)**
- **F stop: F4.3**
- **Resolution: 100 lp/mm at center and corner**
- **Relative illumination rate: more than 70%**
- **Optical distortion: maximum 1.7%**

▶ See page 44



TEC-V7X Field of view (mm)

Working Distance (mm)	Optical Magnification	1.1 inch			1 inch			2/3 inch			
		H	V	D	H	V	D	H	V	D	
182	Wide	0.2525	48.74	48.74	69.12	50.32	38.06	63.28	34.88	26.16	43.6
	Middle	0.3643	33.64	33.64	47.33	34.72	26.3	43.6	24.12	18.1	30.11
	Tele	0.5	24.6	24.6	34.75	25.4	19.246	31.88	17.65	13.26	22
200	Wide	0.2258	54.52	54.52	76.94	56.3	42.56	70.84	39	29.24	48.76
	Middle	0.3258	37.62	37.62	52.95	38.83	29.4	48.78	26.96	20.24	33.67
	Tele	0.4451	27.5	27.5	38.68	28.38	21.51	35.64	19.72	14.81	24.62
300	Wide	0.1413	87.48	87.48	124.06	90.34	68.18	114.1	62.46	46.8	78.178
	Middle	0.2037	60.24	60.24	85.34	62.18	47.06	78.18	42.15	32.38	53.898
	Tele	0.2784	44	44	61.94	45.42	34.3	57.46	31.55	23.69	39.38
400	Wide	0.1037	119.47	119.47	169.98	123.4	93.02	156.05	85.2	63.82	106.71
	Middle	0.1495	82.15	82.15	115.97	84.8	64.16	106.72	58.82	44.12	73.48
	Tele	0.2042	59.99	59.99	84.52	61.92	46.89	77.82	43	32.28	53.7
500	Wide	0.082	151.25	151.24	215.44	156.25	117.67	197.8	107.78	80.68	135.04
	Middle	0.1183	103.92	103.92	146.82	107.28	81.12	135	74.37	55.78	92.94
	Tele	0.1617	75.84	75.84	106.89	78.29	59.28	98.4	54.36	40.8	67.88
577.5	Wide	0.0708	175.21	175.21	250.66	181.4	136.35	229.82	125.08	93.62	156.76
	Middle	0.102	120.57	120.57	170.44	124.47	94.1	156.74	86.28	64.72	107.84
	Tele	0.1398	87.99	87.99	124.04	90.8	68.75	114.16	63.06	47.32	78.74

MANUAL IRIS

MANUAL IRIS

CS-MOUNT

MANUAL IRIS

C-MOUNT

MANUAL IRIS


FIX

MANUAL

WIDE



MODEL NO.	T2314FICS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	2.3
Aperture (F)	1.4-16C
Angle of View (HOR)°	113.3
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 22.8 Rear (φmm) 7.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ34.5 × 35.4
Weight (g)	43




FIX

MANUAL



MODEL NO.	M8513
Format (")	2/3
Mount	C
Focal Length (mm)	8.5
Aperture (F)	1.3-16C
Angle of View (HOR)°	57.4
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 20.0 Rear (φmm) 12.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ39 × 31.6
Weight (g)	50




FIX

MANUAL

WIDE



MODEL NO.	T2616FICS-4
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	1.6-11C
Angle of View (HOR)°	99.6
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 16.4 Rear (φmm) 8.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ34.5 × 34.7
Weight (g)	45



AUTO IRIS

DC DRIVE / VIDEO DRIVE

AUTO IRIS


FIX

MANUAL

IR



MODEL NO.	T0412FICS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	4
Aperture (F)	1.2-16C
Angle of View (HOR)°	63.9
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 15.5 Rear (φmm) 8.5
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ34.5 × 33
Weight (g)	36




FIX

DC

WIDE



MODEL NO.	TG2314FCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	2.3
Aperture (F)	1.4-360C
Angle of View (HOR)°	113.3
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 22.8 Rear (φmm) 7.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ32 × 39.8 × 35.4
Weight (g)	45




FIX

MANUAL

IR



MODEL NO.	T0812FICS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	8
Aperture (F)	1.2-16C
Angle of View (HOR)°	34.7
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 15.0 Rear (φmm) 8.8
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ34.5 × 33
Weight (g)	37




FIX

DC

WIDE



MODEL NO.	TG2616FCS-4
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	1.6-360C
Angle of View (HOR)°	99.6
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 16.4 Rear (φmm) 8.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ32 × 39.8 × 34.7
Weight (g)	47




FIX

MANUAL



MODEL NO.	H1214FICS-3
Format (")	1/2
Mount	CS
Focal Length (mm)	12
Aperture (F)	1.4-16C
Angle of View (HOR)°	30.4
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 13.0 Rear (φmm) 8.8
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ34.5 × 33
Weight (g)	33




FIX

DC

IR




MODEL NO.	TG0412FCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	4
Aperture (F)	1.2-360C
Angle of View (HOR)°	63.9
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 15.5 Rear (φmm) 8.5
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ32 × 39.8 × 33
Weight (g)	38



FIX
DC
IR




MODEL NO.	TG0812FCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	8
Aperture (F)	1.2-360C
Angle of View (HOR)°	34.7
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	15.0
Effective Aperture Rear (φmm)	8.8
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ32 × 39.8 × 33
Weight (g)	39



FIX
DC




MODEL NO.	HG1214FCS-3
Format (")	1/2
Mount	CS
Focal Length (mm)	12
Aperture (F)	1.4-360C
Angle of View (HOR)°	30.4
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	13.0
Effective Aperture Rear (φmm)	8.8
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ32 × 39.8 × 33
Weight (g)	35



FIX
VIDEO
WIDE




MODEL NO.	TG2314AFCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	2.3
Aperture (F)	1.4-360C
Angle of View (HOR)°	113.3
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	22.8
Effective Aperture Rear (φmm)	7.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ32 × 39.8 × 35.4
Weight (g)	48



FIX
VIDEO
WIDE




MODEL NO.	TG2616AFCS-4
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	1.6-360C
Angle of View (HOR)°	99.6
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	16.4
Effective Aperture Rear (φmm)	8.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ32 × 39.8 × 34.7
Weight (g)	50



FIX
VIDEO




MODEL NO.	HG1214AFCS-3
Format (")	1/2
Mount	CS
Focal Length (mm)	12
Aperture (F)	1.4-360C
Angle of View (HOR)°	30.4
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	13.0
Effective Aperture Rear (φmm)	8.8
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ32 × 39.8 × 33
Weight (g)	39



Vari-Focal Lens Comparison


Manual Iris



VARI
MANUAL
WIDE




MODEL NO.	T2Z1816CS
Format (")	1/3
Mount	CS
Focal Length (mm)	1.8-3.6
Aperture (F)	1.6-16C
Angle of View (HOR)°	144.2-79.4
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	22.0
Effective Aperture Rear (φmm)	7.9
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37.4 × 51
Weight (g)	68



VARI
MANUAL
F1.0
ASP




MODEL NO.	T3Z2910CS
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-16C
Angle of View (HOR)°	98.3-35.2
M.O.D. (m)	0.5
Effective Aperture Front (φmm)	18.8
Effective Aperture Rear (φmm)	9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ36.5 × 44.3
Weight (g)	41



VARI
MANUAL
F1.0
ASP
IR




MODEL NO.	T3Z2910CS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-16C
Angle of View (HOR)°	95.0-35.6
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 19.0 Rear (φmm) 8.5
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ36.5 × 44.3
Weight (g)	44



VARI
MANUAL
F1.0
ASP




MODEL NO.	T3Z3510CS
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-16C
Angle of View (HOR)°	81.6-27.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.5 Rear (φmm) 10.1
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ41.6 × 48.8
Weight (g)	63



VARI
MANUAL
F1.0
ASP
IR




MODEL NO.	T3Z3510CS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-16C
Angle of View (HOR)°	81.8-27.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.6 Rear (φmm) 10.2
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ41.6 × 48.8
Weight (g)	63



VARI
MANUAL
ASP
IR




MODEL NO.	T4Z2813CS-IR-2
Format (")	1/3
Mount	CS
Focal Length (mm)	2.8-12
Aperture (F)	1.3-16C
Angle of View (HOR)°	102.2-23.7
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 23.0 Rear (φmm) 7.4
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ40.7 × 56.0
Weight (g)	63



VARI
MANUAL
TELE
ASP




MODEL NO.	T10Z0513CS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	5-50
Aperture (F)	1.3-16C
Angle of View (HOR)°	51.8-5.6
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 29.5 Rear (φmm) 8.7
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ45 × 57.8
Weight (g)	90



VARI
MANUAL
TELE
ASP
IR




MODEL NO.	T5Z8513CS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	8.5-40
Aperture (F)	1.3-16C
Angle of View (HOR)°	33.5-7.1
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 27.0 Rear (φmm) 9.3
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ47.0 × 62.9
Weight (g)	126



VARI
MANUAL
IR




MODEL NO.	H2Z4516CS-2
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-10
Aperture (F)	1.6-16C
Angle of View (HOR)°	81.3-38.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ34 × 43.5
Weight (g)	40



VARI
MANUAL
ASP
IR




MODEL NO.	H3Z4512CS-IR
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-12.5
Aperture (F)	1.2-16C
Angle of View (HOR)°	83.7-30.1
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 19.9 Rear (φmm) 9.9
Front Filter Thread (φMxP=)	-
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ41.6 × 48.8
Weight (g)	66



VARI
MANUAL
TELE
ASP
IR




MODEL NO.	H3Z1014CS
Format (")	1/2
Mount	CS
Focal Length (mm)	10-30
Aperture (F)	1.4-16C
Angle of View (HOR)°	35.8-12.5
M.O.D. (m)	0.6
Effective Aperture	Front (φmm) 26.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ47 × 57.7
Weight (g)	125




※ HG321014 Series 1/2type lenses have no focus shift with or without IR lighting only when used with 1/2type cameras. If these lenses are used with 1/3type cameras, some focus shift may occur with IR lighting.


Vari-Focal Lens Comparison



MODEL NO.	TG2Z1816FCS
Format (")	1/3
Mount	CS
Focal Length (mm)	1.8-3.6
Aperture (F)	1.6-360C
Angle of View (HOR)°	144.2-79.4
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	22.0
Effective Aperture Rear (φmm)	7.9
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ37.4 × 42.6 × 51
Weight (g)	78




MODEL NO.	TG3Z2312FCS
Format (")	1/3
Mount	CS
Focal Length (mm)	2.3-6
Aperture (F)	1.2-360
Angle of View (HOR)°	114.8-48.2
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	19.5
Effective Aperture Rear (φmm)	9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ38.5 × 48 × 51.1
Weight (g)	76



- VARI
- DC
- F1.0
- ASP




MODEL NO.	TG3Z2910FCS
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	98.3-35.2
M.O.D. (m)	0.5
Effective Aperture Front (φmm)	18.8
Effective Aperture Rear (φmm)	9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ33.5 × 46.6 × 44.3
Weight (g)	47



- VARI
- DC
- F1.0
- ASP
- IR




MODEL NO.	TG3Z2910FCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	95.0-35.6
M.O.D. (m)	0.5
Effective Aperture Front (φmm)	19.0
Effective Aperture Rear (φmm)	8.5
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ33.5 × 46.6 × 44.3
Weight (g)	50



- VARI
- DC
- F1.0
- ASP




MODEL NO.	TG3Z3510FCS
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-360
Angle of View (HOR)°	81.6-27.2
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	18.5
Effective Aperture Rear (φmm)	10.1
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ38.5 × 48 × 48.8
Weight (g)	65



- VARI
- DC
- F1.0
- ASP
- IR




MODEL NO.	TG3Z3510FCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-360
Angle of View (HOR)°	81.6-27.2
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	18.6
Effective Aperture Rear (φmm)	10.2
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ38.5 × 48 × 48.8
Weight (g)	65



- VARI
- DC
- ASP
- IR




MODEL NO.	TG4Z2813FCS-IR-2
Format (")	1/3
Mount	CS
Focal Length (mm)	2.8-12
Aperture (F)	1.3-360
Angle of View (HOR)°	102.2-23.7
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	23.0
Effective Aperture Rear (φmm)	7.4
Front Filter Thread (φMxP=)	-
Dimensions (φxHxD) or (WxHxD)mm	φ37.5 × 48 × 56
Weight (g)	71



VARI
DC
TELE
ASP




MODEL NO.	TG10Z0513AFCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	5-50
Aperture (F)	1.3-360C
Angle of View (HOR)°	51.8-5.6
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 29.5 Rear (φmm) 8.7
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxHxL) or (WxHxD)mm	φ45 × 56.2 × 57.8
Weight (g)	100



VARI
DC
TELE
ASP
IR




MODEL NO.	TG5Z8513AFCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	8.5-40
Aperture (F)	1.3-360C
Angle of View (HOR)°	33.5-7.1
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 27.0 Rear (φmm) 9.3
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxHxL) or (WxHxD)mm	φ41.7 × 57.5 × 62.9
Weight (g)	114



VARI
DC
IR




MODEL NO.	HG2Z4516AFCS-2
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-10
Aperture (F)	1.6-360C
Angle of View (HOR)°	81.3-38.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ33.5 × 42.6 × 43.5
Weight (g)	54



VARI
DC
ASP
IR




MODEL NO.	HG3Z4512AFCS-IR
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-12.5
Aperture (F)	1.2-360
Angle of View (HOR)°	83.7-30.1
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 19.9 Rear (φmm) 9.9
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ38.5 × 47.5 × 48.8
Weight (g)	68



VARI
DC
TELE
ASP
IR




MODEL NO.	HG3Z1014AFCS
Format (")	1/2
Mount	CS
Focal Length (mm)	10-30
Aperture (F)	1.4-360C
Angle of View (HOR)°	35.8-12.5
M.O.D. (m)	0.6
Effective Aperture	Front (φmm) 26.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxHxL) or (WxHxD)mm	φ41.7 × 57.5 × 57.7
Weight (g)	120



Vari-Focal Lens Comparison


Video Drive



VARI
VIDEO
WIDE




MODEL NO.	TG2Z1816AFCS
Format (")	1/3
Mount	CS
Focal Length (mm)	1.8-3.6
Aperture (F)	1.6-360C
Angle of View (HOR)°	144.2-79.4
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 22.0 Rear (φmm) 7.9
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37.4 × 42.6 × 51
Weight (g)	83



VARI
VIDEO
F1.0
ASP



MODEL NO.	TG3Z2910AFCS
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	98.3-35.2
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 18.8 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ33.5 × 46.6 × 44.3
Weight (g)	51




* HG3Z1014 Series 1/2type lenses have no focus shift with or without IR lighting only when used with 1/2type cameras. If these lenses are used with 1/3type cameras, some focus shift may occur with IR lighting.

- VARI
- VIDEO
- F1.0
- ASP
- IR




MODEL NO.	TG3Z2910AFCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	2.9-8.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	95.0-35.6
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 19.0 Rear (φmm) 8.5
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ33.5 × 46.6 × 44.3
Weight (g)	54



- VARI
- VIDEO
- F1.0
- ASP




MODEL NO.	TG3Z3510AFCS
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-360
Angle of View (HOR)°	81.6-27.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.5 Rear (φmm) 10.1
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ38.5 × 48 × 48.8
Weight (g)	70



- VARI
- VIDEO
- F1.0
- ASP
- IR




MODEL NO.	TG3Z3510AFCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	3.5-10.5
Aperture (F)	1.0-360
Angle of View (HOR)°	81.8-27.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.6 Rear (φmm) 10.2
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ38.5 × 48 × 48.8
Weight (g)	70



- VARI
- VIDEO
- ASP
- IR




MODEL NO.	TG4Z2813AFCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	2.8-12
Aperture (F)	1.3-360
Angle of View (HOR)°	102.2-23.7
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 23.0 Rear (φmm) 7.4
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ37.5 × 48 × 56
Weight (g)	74



- VARI
- VIDEO
- TELE
- ASP




MODEL NO.	TG10Z0513AFCS-3
Format (")	1/3
Mount	CS
Focal Length (mm)	5-50
Aperture (F)	1.3-360C
Angle of View (HOR)°	51.8-5.6
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 29.5 Rear (φmm) 8.7
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ45 × 56.2 × 57.8
Weight (g)	103



- VARI
- VIDEO
- TELE
- ASP
- IR




MODEL NO.	TG5Z8513AFCS-IR
Format (")	1/3
Mount	CS
Focal Length (mm)	8.5-40
Aperture (F)	1.3-360C
Angle of View (HOR)°	33.5-7.1
M.O.D. (m)	0.8
Effective Aperture	Front (φmm) 27.0 Rear (φmm) 9.3
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ41.7 × 57.5 × 62.9
Weight (g)	115



- VARI
- VIDEO
- IR




MODEL NO.	HG2Z4516AFCS-2
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-10
Aperture (F)	1.6-360C
Angle of View (HOR)°	81.3-38.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ33.5 × 42.6 × 43.5
Weight (g)	56



- VARI
- VIDEO
- ASP
- IR




MODEL NO.	HG3Z4512AFCS-IR
Format (")	1/2
Mount	CS
Focal Length (mm)	4.5-12.5
Aperture (F)	1.2-360
Angle of View (HOR)°	83.7-30.1
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 19.9 Rear (φmm) 9.9
Front Filter Thread (φMxP=)	-
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ38.5 × 47.5 × 48.8
Weight (g)	73



- VARI
- VIDEO
- ASP
- TELE
- IR



MODEL NO.	HG3Z1014AFCS
Format (")	1/2
Mount	CS
Focal Length (mm)	10-30
Aperture (F)	1.4-360C
Angle of View (HOR)°	35.8-12.5
M.O.D. (m)	0.6
Effective Aperture	Front (φmm) 26.6 Rear (φmm) 9.0
Front Filter Thread (φMxP=)	37.5 × 0.5
Dimensions (φxH, (φxHxD) or (WxHxD)mm)	φ41.7 × 57.5 × 57.7
Weight (g)	125



※ HG3Z1014 Series 1/2type lenses have no focus shift with or without IR lighting only when used with 1/2type cameras. If these lenses are used with 1/3type cameras, some focus shift may occur with IR lighting.

PINHOLE

PINHOLE

MANUAL IRIS / DC DRIVE / VIDEO DRIVE


MANUAL IRIS

FIX

MANUAL



MODEL NO.	T2625CS-P
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	2.5-32C
Angle of View (HOR)°	83.2
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 4.8
	Rear (φmm) 11.5
Front Filter Thread (φMxP=)	-
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ34.5 × 73.5
Weight (g)	80




FIX

DC



MODEL NO.	TG2625FCS-P
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	2.5-360C
Angle of View (HOR)°	83.2
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 4.8
	Rear (φmm) 11.5
Front Filter Thread (φMxP=)	-
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ34.5 × 39.8 × 73.5
Weight (g)	82




FIX

VIDEO



MODEL NO.	TG2625AFCS-P
Format (")	1/3
Mount	CS
Focal Length (mm)	2.6
Aperture (F)	2.5-360C
Angle of View (HOR)°	83.2
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 4.8
	Rear (φmm) 11.5
Front Filter Thread (φMxP=)	-
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ34.5 × 39.8 × 73.5
Weight (g)	85



VIDEO DRIVE

MANUAL ZOOM

MANUAL ZOOM


MANUAL IRIS / DC DRIVE / VIDEO DRIVE

ZOOM

MANUAL



MODEL NO.	H6Z0812
Format (")	1/2
Mount	C
Focal Length (mm)	8-48
Aperture (F)	1.2-16C
Angle of View (HOR)°	44.6-8.0
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 32.9
	Rear (φmm) 16.6
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ51.8 × 97
Weight (g)	305



MANUAL ZOOM

MANUAL IRIS / DC DRIVE / VIDEO DRIVE


MANUAL ZOOM

ZOOM

MANUAL



MODEL NO.	M6Z1212-3S
Format (")	2/3
Mount	C
Focal Length (mm)	12.5-75
Aperture (F)	1.2-16C
Angle of View (HOR)°	38.3-6.7
M.O.D. (m)	1.0
Effective Aperture	Front (φmm) 46.5
	Rear (φmm) 15.6
Front Filter Thread (φMxP=)	55.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ59.9 × 114.5
Weight (g)	483



ZOOM


DC

F1.0

SPOT FILTER



MODEL NO.	T6Z5710AIDC-CS
Format (")	1/3
Mount	CS
Focal Length (mm)	5.7-34.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	45.9-8.1
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 41.0
	Rear (φmm) 10.2
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ53 × 64 × 82.5
Weight (g)	295




ZOOM

DC

SPOT FILTER



MODEL NO.	H6Z0812AIDC
Format (")	1/2
Mount	C
Focal Length (mm)	8-48
Aperture (F)	1.2-560C
Angle of View (HOR)°	44.6-8.0
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 39.2
	Rear (φmm) 16.6
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ52.6 × 64 × 97
Weight (g)	295



ZOOM


VIDEO

F1.0

SPOT FILTER



MODEL NO.	T6Z5710AIVD-CS
Format (")	1/3
Mount	CS
Focal Length (mm)	5.7-34.2
Aperture (F)	1.0-360C
Angle of View (HOR)°	45.9-8.1
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 41.0
	Rear (φmm) 10.2
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ53 × 64 × 82.5
Weight (g)	295




ZOOM

VIDEO

SPOT FILTER



MODEL NO.	H6Z0812AIVD
Format (")	1/2
Mount	C
Focal Length (mm)	8-48
Aperture (F)	1.2-560C
Angle of View (HOR)°	44.6-8.0
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 39.2
	Rear (φmm) 16.6
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (φ(D), φ(HxL) or (WxHxD)mm)	φ52.6 × 64 × 97
Weight (g)	295



T6Z5710 Series
f 5.7-34.2mm, F1.0

x6




T10Z5712 Series
f 5.7-57mm, F1.2


x10



Format (")	1/3
Mount	CS
Focal Length (mm)	5.7-34.2
Angle of View (HOR)°	45.9-8.1
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 41.0
	Rear (φmm) 10.2
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (WxHxD)mm	68.5 × 76.3 × 82.5



Format (")	1/3
Mount	CS
Focal Length (mm)	5.7-57
Angle of View (HOR)°	44.6-4.8
M.O.D. (m)	1.8
Effective Aperture	Front (φmm) 45.0
	Rear (φmm) 8.6
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (WxHxD)mm	68.5 × 76.3 × 88



NO.	MODEL NO.				Aperture (F)	Weight (g)
1	T6Z5710M-CS	ZOOM	3 MOTOR	F1.0	1.0-16C	430
2	T6Z5710MP-CS	ZOOM	3 MOTOR	F1.0	PRESET	470
3	T6Z5710MS-CS	ZOOM	3 MOTOR	F1.0	SPOT FILTER	430
4	T6Z5710MSP-CS	ZOOM	3 MOTOR	F1.0	PRESET SPOT FILTER	470
5	T6Z5710AMS-CS	ZOOM	VIDEO	F1.0	SPOT FILTER	450
6	T6Z5710AMSP-CS	ZOOM	VIDEO	F1.0	PRESET SPOT FILTER	490
7	T6Z5710DC-CS	ZOOM	DC	F1.0	SPOT FILTER	440
8	T6Z5710PDC-CS	ZOOM	DC	F1.0	PRESET SPOT FILTER	480

NO.	MODEL NO.				Aperture (F)	Weight (g)
1	T10Z5712M-CS	ZOOM	3 MOTOR		1.2-22C	450
2	T10Z5712MP-CS	ZOOM	3 MOTOR	PRESET	1.2-22C	490
3	T10Z5712MS-CS	ZOOM	3 MOTOR	SPOT FILTER	1.2-560C	450
4	T10Z5712MSP-CS	ZOOM	3 MOTOR	PRESET SPOT FILTER	1.2-560C	490
5	T10Z5712AMS-CS	ZOOM	VIDEO	SPOT FILTER	1.2-560C	470
6	T10Z5712AMSP-CS	ZOOM	VIDEO	PRESET SPOT FILTER	1.2-560C	510
7	T10Z5712DC-CS	ZOOM	DC	SPOT FILTER	1.2-560C	460
8	T10Z5712PDC-CS	ZOOM	DC	PRESET SPOT FILTER	1.2-560C	500

ZOOM LENSES


1/3" MOTORIZED ZOOM

T21Z5816 Series
f 5.8-121.8mm, F1.6

x21



Format (")	1/3
Mount	CS
Focal Length (mm)	5.8-121.8
Angle of View (HOR)°	44.8-2.3
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 53.2
	Rear (φmm) 10.6
Front Filter Thread (φMxP=)	62.0 × 0.75
Dimensions (WxHxD)mm	70 × 81 × 126.5



NO.	MODEL NO.	Aperture (F)	Weight (g)
1	T21Z5816M-CS	ZOOM 3 MOTOR	1.6-22C 665
2	T21Z5816MP-CS	ZOOM 3 MOTOR PRESET	1.6-22C 700
3	T21Z5816MS-CS	ZOOM 3 MOTOR SPOT FILTER	1.6-560C 665
4	T21Z5816MSP-CS	ZOOM 3 MOTOR PRESET SPOT FILTER	1.6-560C 700
5	T21Z5816AMS-CS2	ZOOM VIDEO SPOT FILTER	1.6-560C 700
6	T21Z5816AMSP-CS2	ZOOM VIDEO PRESET SPOT FILTER	1.6-560C 740
7	T21Z5816DC-CS	ZOOM DC SPOT FILTER	1.6-560C 650
8	T21Z5816PDC-CS	ZOOM DC PRESET SPOT FILTER	1.6-560C 690

1/3" MOTORIZED ZOOM


ZOOM LENSES

T34Z5518 Series
f 5.5-187mm, F1.8

x34



Format (")	1/3
Mount	CS
Focal Length (mm)	5.5-187
Angle of View (HOR)°	46.6-1.5
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 70.0
	Rear (φmm) 9.1
Front Filter Thread (φMxP=)	77.0 × 0.75
Dimensions (WxHxD)mm	82 × 97.4 × 160



NO.	MODEL NO.	Aperture (F)	Weight (g)
1	T34Z5518AMS-CS	ZOOM VIDEO SPOT FILTER	1.8-560C 1160
2	T34Z5518AMSP-CS	ZOOM VIDEO PRESET SPOT FILTER	1.8-560C 1190
3	T34Z5518AMSR-CS	ZOOM VIDEO SPOT FILTER OVERRIDE	1.8-560C 1150
4	T34Z5518AMSPR-CS	ZOOM VIDEO PRESET SPOT FILTER OVERRIDE	1.8-560C 1180
5	T34Z5518DC-CS	ZOOM DC SPOT FILTER	1.8-560C 1110
6	T34Z5518PDC-CS	ZOOM DC PRESET SPOT FILTER	1.8-560C 1150

ZOOM LENSES


1/2" MOTORIZED ZOOM

H6Z0812 Series
f 8-48mm, F1.2

x6



Format (")	1/2
Mount	C
Focal Length (mm)	8-48
Angle of View (HOR)°	44.6-8.0
M.O.D. (m)	1.2
Effective Aperture	Front (φmm) 39.2
	Rear (φmm) 16.6
Front Filter Thread (φMxP=)	49.0 × 0.75
Dimensions (WxHxD)mm	66 × 73.5 × 97



NO.	MODEL NO.	Aperture (F)		Weight (g)
1	H6Z0812M	ZOOM	3 MOTOR	400
2	H6Z0812MP	ZOOM	3 MOTOR PRESET	440
3	H6Z0812MS	ZOOM	3 MOTOR SPOT FILTER	400
4	H6Z0812MSP	ZOOM	3 MOTOR PRESET SPOT FILTER	440
5	H6Z0812AMS	ZOOM	VIDEO SPOT FILTER	420
6	H6Z0812AMSP	ZOOM	VIDEO PRESET SPOT FILTER	460

1/2" MOTORIZED ZOOM


ZOOM LENSES

H10Z0812 Series
f 8-80mm, F1.2

x10



Format (")	1/2
Mount	C
Focal Length (mm)	8-80
Angle of View (HOR)°	44.0-4.7
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 54.0
	Rear (φmm) 14.0
Front Filter Thread (φMxP=)	62.0 × 0.75
Dimensions (WxHxD)mm	70 × 81 × 123.5



NO.	MODEL NO.	Aperture (F)		Weight (g)
1	H10Z0812M	ZOOM	3 MOTOR	635
2	H10Z0812MP	ZOOM	3 MOTOR PRESET	670
3	H10Z0812MS	ZOOM	3 MOTOR SPOT FILTER	635
4	H10Z0812MSP	ZOOM	3 MOTOR PRESET SPOT FILTER	670
5	H10Z0812AMS-2	ZOOM	VIDEO SPOT FILTER	670
6	H10Z0812AMSP-2	ZOOM	VIDEO PRESET SPOT FILTER	710

ZOOM LENSES


1/2" MOTORIZED ZOOM

H10Z1218 Series
f 12-120mm, F1.8

x 10



Format (")	1/2
Mount	C
Focal Length (mm)	12-120
Angle of View (HOR)°	29.4-3.1
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 54.0
	Rear (φmm) 9.2
Front Filter Thread (φMxP=)	62.0 × 0.75
Dimensions (WxHxD)mm	70 × 81 × 123.5



NO.	MODEL NO.			Aperture (F)	Weight (g)
1	H10Z1218M	ZOOM	3 MOTOR	1.8-22C	635
2	H10Z1218MP	ZOOM	3 MOTOR PRESET	1.8-22C	670
3	H10Z1218MS	ZOOM	3 MOTOR SPOT FILTER	1.8-560C	635
4	H10Z1218MSP	ZOOM	3 MOTOR PRESET SPOT FILTER	1.8-560C	670
5	H10Z1218AMS-2	ZOOM	VIDEO SPOT FILTER	1.8-560C	670
6	H10Z1218AMSP-2	ZOOM	VIDEO PRESET SPOT FILTER	1.8-560C	710
7	H10Z1218DC	ZOOM	DC SPOT FILTER	1.8-560C	630
8	H10Z1218PDC	ZOOM	DC PRESET SPOT FILTER	1.8-560C	670

1/2" MOTORIZED ZOOM


ZOOM LENSES

H16Z7516 Series
f 7.5-120mm, F1.6

x 16



Format (")	1/2
Mount	C
Focal Length (mm)	7.5-120
Angle of View (HOR)°	46.6-3.2
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 66.4
	Rear (φmm) 13.5
Front Filter Thread (φMxP=)	72.0 × 0.75
Dimensions (WxHxD)mm	82 × 97.4 × 149




NO.	MODEL NO.			Aperture (F)	Weight (g)
1	H16Z7516AMS	ZOOM	VIDEO SPOT FILTER	1.6-560C	1050
2	H16Z7516AMSP	ZOOM	VIDEO PRESET SPOT FILTER	1.6-560C	1080
3	H16Z7516AMSR	ZOOM	VIDEO SPOT FILTER OVERRIDE	1.6-560C	1040
4	H16Z7516AMSPR	ZOOM	VIDEO PRESET SPOT FILTER OVERRIDE	1.6-560C	1070
5	H16Z7516DC	ZOOM	DC SPOT FILTER	1.6-560C	1010
6	H16Z7516PDC	ZOOM	DC PRESET SPOT FILTER	1.6-560C	1050

H16Z7516-IR Series
f 7.5-120mm, F1.6

x 16



Format (")	1/2
Mount	C
Focal Length (mm)	7.5-120
Angle of View (HOR)°	47.0-3.1
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 68.0 Rear (φmm) 14.3
Front Filter Thread (φMxP=)	77.0 × 0.75
Dimensions (WxHxD)mm	82 × 97.4 × 161.5



NO.	MODEL NO.	Features				Aperture (F)	Weight (g)	
1	H16Z7516AMS-IR	ZOOM	VIDEO	SPOT FILTER	IR	1.6-560C	1160	
2	H16Z7516AMSP-IR	ZOOM	VIDEO	PRESET	SPOT FILTER	IR	1180	
3	H16Z7516AMSR-IR	ZOOM	VIDEO	SPOT FILTER	OVERRIDE	IR	1185	
4	H16Z7516AMSPR-IR	ZOOM	VIDEO	PRESET	SPOT FILTER	OVERRIDE	IR	1215

Features of H16Z7516-IR series

Infrared light increases at night because the wavelength distribution changes greatly between day and night. In case of night surveillance with infrared lighting, standard CCTV lenses cause a focus shift because of the difference in wavelength distribution, even when focused properly during the day.


Computar's new IR zoom lens utilizes a special optical glass material which minimizes light dispersion. As a result, refocusing is not required when used at night with infrared lighting. The lens also has a special multi-coating on all lens elements so that the lens transmits more light up to the infrared region. This provides a much more vivid picture when used at night with Day&Night cameras or ultra high sensitivity cameras.

H30Z1015 Series
f 10-300mm, F1.5

x 30



Format (")	1/2
Mount	C
Focal Length (mm)	10-300
Angle of View (HOR)°	35.5-1.25
M.O.D. (m)	2.2
Effective Aperture	Front (φmm) 94.0 Rear (φmm) 14.8
Front Filter Thread (φMxP=)	100 × 1
Dimensions (WxHxD)mm	125 × 144.5 × 246.5



NO.	MODEL NO.	Features				Aperture (F)	Weight (g)
1	H30Z1015AMS	ZOOM	VIDEO	SPOT FILTER		1.5-560C	3170
2	H30Z1015AMSP	ZOOM	VIDEO	PRESET	SPOT FILTER	1.5-560C	3220
3	H30Z1015AMSR	ZOOM	VIDEO	SPOT FILTER	OVERRIDE	1.5-560C	3175
4	H30Z1015AMSPR	ZOOM	VIDEO	PRESET	SPOT FILTER	OVERRIDE	3225

Features of H30Z1015 series

This lens provides powerful zoom ratio(10-300mm) and the fastest F-stop (F1.5) in the CCTV market, making it ideal for long distance or low light surveillance. Typical applications include highway and traffic monitoring, port and harbor surveillance, airport surveillance and border patrol.


ZOOM LENSES

1/2" MOTORIZED ZOOM

H60Z1238 Series
f 12.5-750mm, F3.8 / f 25-1500mm, F7.6(w/2x extender) **x60**



Format (")	1/2
Mount	C
Focal Length (mm)	12.5-750 25-1500(with 2x extender.)
Angle of View (HOR)°	28.7-0.48
M.O.D. (m)	5.0
Effective Aperture	Front (φmm) 98.8 Rear (φmm) 13.6
Front Filter Thread (φMxP=)	107 × 1
Dimensions (WxHxD)mm	154 × 137 × 354



NO.	MODEL NO.	Aperture (F)	Weight (g)
1	H60Z1238A	3.8-3000	5100
2	H60Z1238A-IR	3.8-3000	5200
3	H60Z1238A-IRF	3.8-3000	5200


1/2" MEGAPIXEL MOTORIZED ZOOM

MEGAPIXEL ZOOM

H21Z1016-MP Series
f 10-210mm, F1.6 **x21**



Format (")	1/2
Mount	C
Focal Length (mm)	10-210
Angle of View (HOR)°	35.4-1.72
M.O.D. (m)	2.0
Effective Aperture	Front (φmm) 68.0 Rear (φmm) 11.8
Front Filter Thread (φMxP=)	72.0 × 0.75
Dimensions (WxHxD)mm	84 × 94.5 × 181.5



NO.	MODEL NO.	Aperture (F)	Weight (g)
1	H21Z1016AMS-MP	1.6-1000	1050
2	H21Z1016AMSP-MP	1.6-1000	1100
3	H21Z1016DC-MP	1.6-1000	1050
4	H21Z1016PDC-MP	1.6-1000	1100

MEGAPIXEL ZOOM


1/1.8" MEGAPIXEL MOTORIZED ZOOM

E24Z1018-MP Series f 10-240mm, F1.8

x24



Format (")	1/1.8
Mount	C
Focal Length (mm)	10-240
Angle of View (HOR)°	39.0-1.7
M.O.D. (m)	3.0
Effective Aperture	Front (φmm) 66.0 Rear (φmm) 13.0
Front Filter Thread (φMxP=)	77 × 1
Dimensions (WxHxD)mm	101 × 99.4 × 198.2



NO.	MODEL NO.	Features			Aperture (F)	Weight (g)	
1	E24Z1018M-MP	ZOOM	3 MOTOR	3MP	1.8-500C	2080	
2	E24Z1018MP-MP	ZOOM	3 MOTOR	PRESET	1.8-500C	2120	
3	E24Z1018MS-MP	ZOOM	3 MOTOR	SPOT FILTER	1.8-500C	2080	
4	E24Z1018MSP-MP	ZOOM	3 MOTOR	PRESET	SPOT FILTER	1.8-500C	2120
5	E24Z1018AMS-MP	ZOOM	VIDEO	SPOT FILTER	1.8-500C	2020	
6	E24Z1018AMSP-MP	ZOOM	VIDEO	PRESET	SPOT FILTER	1.8-500C	2060
7	E24Z1018DC-MP	ZOOM	DC	SPOT FILTER	1.8-500C	2020	
8	E24Z1018PDC-MP	ZOOM	DC	PRESET	SPOT FILTER	1.8-500C	2060
9	E24Z1018K-MP	ZOOM	P-iris	3MP	1.8-500C	2010	
10	E24Z1018KP-MP	ZOOM	P-iris	PRESET	3MP	1.8-500C	2050

※ Override and Iris preset models are acceptable. Please contact us.
 ※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

1/1.8" MEGAPIXEL MOTORIZED ZOOM


MEGAPIXEL ZOOM

E24Z1018-MPIR Series f 10-240mm, F1.8

x24



Format (")	1/1.8
Mount	C
Focal Length (mm)	10-240
Angle of View (HOR)°	39.0-1.7
M.O.D. (m)	3.0
Effective Aperture	Front (φmm) 66.0 Rear (φmm) 13.0
Front Filter Thread (φMxP=)	77 × 1
Dimensions (WxHxD)mm	101 × 99.4 × 198.2



NO.	MODEL NO.	Features			Aperture (F)	Weight (g)	
1	E24Z1018M-MPIR	ZOOM	3 MOTOR	3MP	1.8-500C	2160	
2	E24Z1018MP-MPIR	ZOOM	3 MOTOR	PRESET	3MP	2200	
3	E24Z1018MS-MPIR	ZOOM	3 MOTOR	SPOT FILTER	3MP	2160	
4	E24Z1018MSP-MPIR	ZOOM	3 MOTOR	PRESET	SPOT FILTER	1.8-500C	2200
5	E24Z1018AMS-MPIR	ZOOM	VIDEO	SPOT FILTER	3MP	2100	
6	E24Z1018AMSP-MPIR	ZOOM	VIDEO	PRESET	SPOT FILTER	1.8-500C	2140
7	E24Z1018DC-MPIR	ZOOM	DC	SPOT FILTER	3MP	2100	
8	E24Z1018PDC-MPIR	ZOOM	DC	PRESET	SPOT FILTER	1.8-500C	2140
9	E24Z1018K-MPIR	ZOOM	P-iris	3MP	1.8-500C	2090	
10	E24Z1018KP-MPIR	ZOOM	P-iris	PRESET	3MP	1.8-500C	2130

※ Override and Iris preset models are acceptable. Please contact us.
 ※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

ZOOM LENSES


1/2" MEGAPIXEL MOTORIZED ZOOM

H35Z1015-MP Series f 10-350mm, F1.5

x 35



Format (")	1/2
Mount	C
Focal Length (mm)	10-350
Angle of View (HOR)°	35.30-1.05
M.O.D. (m)	2.5
Effective Aperture	Front (φmm) 80.1
	Rear (φmm) 17.3
Front Filter Thread (φMxP=)	86 × 1
Dimensions (WxHxD)mm	97 × 109 × 245



NO.	MODEL NO.						Aperture (F)	Weight (g)
1	H35Z1015AMS-MP	ZOOM	VIDEO	SPOT FILTER	2MP	1.5-1000	1830	
2	H35Z1015AMSP-MP	ZOOM	VIDEO	PRESET	SPOT FILTER	2MP	1830	
3	H35Z1015DC-MP	ZOOM	DC	SPOT FILTER	2MP	1.5-1000	1830	
4	H35Z1015PDC-MP	ZOOM	DC	PRESET	SPOT FILTER	2MP	1830	

1/2" MEGAPIXEL MOTORIZED ZOOM

MEGAPIXEL ZOOM


H62Z1235-MP Series

f 12.5-775mm, F3.5 / f 25-1550mm, F7.0(w/2 x extender)

x 62



Format (")	1/2
Mount	C
Focal Length (mm)	12.5-775 25-1550(with 2x extender.)
Angle of View (HOR)°	28.77-0.47
M.O.D. (m)	5.0
Effective Aperture	Front (φmm) 98.5
	Rear (φmm) 17.5
Front Filter Thread (φMxP=)	107 × 1
Dimensions (WxHxD)mm	150 × 135 × 367.5



NO.	MODEL NO.						Aperture (F)	Weight (g)
1	H62Z1235AMP-MP	ZOOM	VIDEO	PRESET	2MP	1.6-22C	5350	
2	H62Z1235AMP-MP-EX	ZOOM	VIDEO	PRESET	2MP	Extender	5550	
3	H62Z1235AMP-MPIR	ZOOM	VIDEO	PRESET	2MP	IR	Fog through	
4	H62Z1235AMP-MPIR-EX	ZOOM	VIDEO	PRESET	2MP	Extender	IR	Fog through
5	H62Z1235PDC-MP	ZOOM	DC	PRESET	2MP	1.6-560C	5350	
6	H62Z1235PDC-MP-EX	ZOOM	DC	PRESET	2MP	Extender	1.6-560C	5550
7	H62Z1235PDC-MPIR	ZOOM	DC	PRESET	2MP	IR	Fog through	
8	H62Z1235PDC-MPIR-EX	ZOOM	DC	PRESET	2MP	Extender	IR	Fog through

※Non-Preset model is acceptable. Please contact us.


FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

- VARI
- DC
- ASP
- IR
- 1MP
- SECURITY




MODEL NO.	TG4Z2816FCS-MPIR
Format (")	1/3
Mount	CS
Focal Length (mm)	2.8-12
Aperture (F)	1.6-360
Angle of View (HOR)°	102.2-23.7
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 23.0
	Rear (φmm) 7.4
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ37.5 × 48 × 56
Weight (g)	71



- VARI
- MANUAL
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	T3Z0312CS-MPIR
Format (")	1/3
Mount	CS
Focal Length (mm)	3-8
Aperture (F)	1.2-16C
Angle of View (HOR)°	90.7-35.2
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 20.9
	Rear (φmm) 10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ40 × 55
Weight (g)	54.5



- VARI
- MANUAL
- 1MP
- SECURITY




MODEL NO.	H2Z0414C-MP
Format (")	1/2
Mount	C
Focal Length (mm)	4-8
Aperture (F)	1.4-16C
Angle of View (HOR)°	90.4-47.0
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 22.2
	Rear (φmm) 10.7
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ41.6 × 48.8
Weight (g)	72



- VARI
- MANUAL
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	A3Z3112CS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	3.1-8
Aperture (F)	1.2-16C
Angle of View (HOR)°	95.9-38.7
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 20.9
	Rear (φmm) 10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ40 × 55
Weight (g)	52.5



- VARI
- DC
- 1MP
- SECURITY




MODEL NO.	HG2Z0414FC-MP
Format (")	1/2
Mount	C
Focal Length (mm)	4-8
Aperture (F)	1.4-360
Angle of View (HOR)°	90.4-47.0
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 22.2
	Rear (φmm) 10.7
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ38.5 × 48 × 48.8
Weight (g)	75



- VARI
- MANUAL
- TELE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	A4Z1214CS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	12.5-50
Aperture (F)	1.4-16C
Angle of View (HOR)°	24.0-6.2
M.O.D. (m)	1.0
Effective Aperture	Front (φmm) 21.7
	Rear (φmm) 9.1
Front Filter Thread (φMxP=)	40 × 0.5
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ49 × 58.2
Weight (g)	80



- VARI
- MANUAL
- 1MP
- SECURITY




MODEL NO.	M3Z1228C-MP
Format (")	2/3
Mount	C
Focal Length (mm)	12-36
Aperture (F)	2.8-16C
Angle of View (HOR)°	41.0-13.6
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 27.2
	Rear (φmm) 12.1
Front Filter Thread (φMxP=)	35.5 × 0.5
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ41.6 × 53
Weight (g)	105



- VARI
- MANUAL
- IR
- 5MP
- SECURITY
- HDTV 1080



MODEL NO.	E3Z4518CS-MPIR
Format (")	1/1.8
Mount	CS
Focal Length (mm)	4.5-13.2
Aperture (F)	1.8-16C
Angle of View (HOR)°	105.3-35.3
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 25.1
	Rear (φmm) 10.0
Front Filter Thread (φMxP=)	-
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ42 × 61
Weight (g)	148




※ Please note M3Z1228C-MP is produced to order

- VARI
- DC
- 1MP
- SECURITY




MODEL NO.	MG3Z1228FC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	12-36
Aperture (F)	2.8-360
Angle of View (HOR)°	41.0-13.6
M.O.D. (m)	0.2
Effective Aperture	Front (φmm) 27.2
	Rear (φmm) 12.1
Front Filter Thread (φMxP=)	35.5 × 0.5
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ41.6 × 48 × 53
Weight (g)	99



- VARI
- MANUAL
- TELE
- ASP
- 3MP
- SECURITY
- HDTV 1080



MODEL NO.	H5Z2518C-MP
Format (")	1/2
Mount	C
Focal Length (mm)	25-135
Aperture (F)	1.8-16C
Angle of View (HOR)°	14.5-2.8
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 44.7
	Rear (φmm) 12.2
Front Filter Thread (φMxP=)	φ52 × 0.75
Dimensions (φxD1, φxHxD2) or (WxHxD)mm	φ54 × 118
Weight (g)	411



※ Please note MG3Z1228FC-MP is produced to order


FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

- VARI
- DC
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	TG3Z0312FCS-MPIR
Format (")	1/3
Mount	CS
Focal Length (mm)	3-8
Aperture (F)	1.2-360C
Angle of View (HOR)°	90.7-35.2
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	20.9
Rear (φmm)	10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37 × 48.2 × 55
Weight (g)	59



- VARI
- DC
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	AG3Z3112FCS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	3.1-8
Aperture (F)	1.2-360C
Angle of View (HOR)°	95.9-38.7
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	20.9
Rear (φmm)	10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37 × 48.2 × 55
Weight (g)	59



- VARI
- DC
- TELE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	AG4Z1214FCS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	12.5-50
Aperture (F)	1.4-360C
Angle of View (HOR)°	24.0-6.2
M.O.D. (m)	1.0
Effective Aperture Front (φmm)	21.7
Rear (φmm)	9.1
Front Filter Thread (φMxP=)	40 × 0.5
Dimensions (φxHxL) or (WxHxD)mm	φ46 × 59.3 × 58.4
Weight (g)	83



- VARI
- DC
- TELE
- ASP
- 3MP
- SECURITY
- HDTV 1080




MODEL NO.	HG5Z2518FC-MP
Format (")	1/2
Mount	C
Focal Length (mm)	25-135
Aperture (F)	1.8-360C
Angle of View (HOR)°	14.5-2.8
M.O.D. (m)	1.5
Effective Aperture Front (φmm)	44.7
Rear (φmm)	12.2
Front Filter Thread (φMxP=)	φ52 × 0.75
Dimensions (φxHxL) or (WxHxD)mm	φ54 × 65 × 118
Weight (g)	402



- VARI
- P-iris
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080



MODEL NO.	TG3Z0312KCS-MPIR
Format (")	1/3
Mount	CS
Focal Length (mm)	3-8
Aperture (F)	1.2-16C
Angle of View (HOR)°	90.7-35.2
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	20.9
Rear (φmm)	10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37 × 48.2 × 55
Weight (g)	57




※ Please note TG3Z0312KCS-MPIR is produced to order.
※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

- VARI
- P-iris
- WIDE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080



MODEL NO.	AG3Z3112KCS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	3.1-8
Aperture (F)	1.2-16C
Angle of View (HOR)°	95.9-38.7
M.O.D. (m)	0.3
Effective Aperture Front (φmm)	20.9
Rear (φmm)	10.5
Front Filter Thread (φMxP=)	-
Dimensions (φxHxL) or (WxHxD)mm	φ37 × 48.2 × 55
Weight (g)	57




※ Please note AG3Z3112KCS-MPIR is produced to order.
※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

- VARI
- P-iris
- TELE
- ASP
- IR
- 3MP
- SECURITY
- HDTV 1080



MODEL NO.	AG4Z1214KCS-MPIR
Format (")	1/2.7
Mount	CS
Focal Length (mm)	12.5-50
Aperture (F)	1.4-16C
Angle of View (HOR)°	24.0-6.2
M.O.D. (m)	1.0
Effective Aperture Front (φmm)	21.7
Rear (φmm)	9.1
Front Filter Thread (φMxP=)	40 × 0.5
Dimensions (φxHxL) or (WxHxD)mm	φ46 × 59.3 × 58.4
Weight (g)	81



※ Please note AG4Z1214KCS-MPIR is produced to order.
※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.


FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

- FIX
- MANUAL
- WIDE
- 1.5MP
- FA




MODEL NO.	H0514-MP2
Format (")	1/2
Mount	C
Focal Length (mm)	5
Aperture (F)	1.4-16C
Angle of View (HOR)°	65.5
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 27.8
	Rear (φmm) 14.8
Front Filter Thread (φMxP=)	43.0 × 0.75
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ44.5 × 45.5
Weight (g)	102



- FIX
- MANUAL
- 1.5MP
- SECURITY
- FA




MODEL NO.	M0814-MP2
Format (")	2/3
Mount	C
Focal Length (mm)	8
Aperture (F)	1.4-16C
Angle of View (HOR)°	56.3
M.O.D. (m)	0.1
Effective Aperture	Front (φmm) 21.5
	Rear (φmm) 12.0
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.5 × 28.2
Weight (g)	63



- FIX
- MANUAL
- 1.5MP
- SECURITY
- FA




MODEL NO.	M1214-MP2
Format (")	2/3
Mount	C
Focal Length (mm)	12
Aperture (F)	1.4-16C
Angle of View (HOR)°	40.4
M.O.D. (m)	0.15
Effective Aperture	Front (φmm) 21.0
	Rear (φmm) 13.0
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.5 × 28.2
Weight (g)	62



- FIX
- MANUAL
- 1.5MP
- SECURITY
- FA




MODEL NO.	M1614-MP2
Format (")	2/3
Mount	C
Focal Length (mm)	16
Aperture (F)	1.4-16C
Angle of View (HOR)°	30.8
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 18.5
	Rear (φmm) 13.2
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.5 × 28.2
Weight (g)	60



- FIX
- MANUAL
- 1.5MP
- SECURITY
- FA




MODEL NO.	M2514-MP2
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.4-16C
Angle of View (HOR)°	20.0
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 17.8
	Rear (φmm) 12.0
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.5 × 36.0
Weight (g)	71



- FIX
- MANUAL
- 1.5MP
- FA




MODEL NO.	M3514-MP
Format (")	2/3
Mount	C
Focal Length (mm)	35
Aperture (F)	1.4-16C
Angle of View (HOR)°	13.9
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 24.0
	Rear (φmm) 12.0
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.0 × 38.2
Weight (g)	87



- FIX
- MANUAL
- 1.5MP
- SECURITY
- FA




MODEL NO.	M5018-MP2
Format (")	2/3
Mount	C
Focal Length (mm)	50
Aperture (F)	1.8-16C
Angle of View (HOR)°	10.5
M.O.D. (m)	0.5
Effective Aperture	Front (φmm) 25.5
	Rear (φmm) 9.6
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ33.5 × 38.2
Weight (g)	85



- FIX
- MANUAL
- TELE
- 1.5MP
- FA




MODEL NO.	M7528-MP
Format (")	2/3
Mount	C
Focal Length (mm)	75
Aperture (F)	2.8-16C
Angle of View (HOR)°	6.8
M.O.D. (m)	0.3
Effective Aperture	Front (φmm) 24.8
	Rear (φmm) 13.6
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxD1, φxHxD2 or WxHxD)mm	φ35.0 × 57.75
Weight (g)	113



- FIX
- MANUAL
- 5MP
- FA




MODEL NO.	M1620-MPW2
Format (")	2/3
Mount	C
Focal Length (mm)	16
Aperture (F)	2.0-16
Angle of View (HOR)°	30.7
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	18.0
Rear (φmm)	11.0
Front Filter Thread (φMxP=)	27.0 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ29 × 33.53
Weight (g)	53



- FIX
- MANUAL
- 5MP
- FA




MODEL NO.	M2518-MPW2
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.8-16
Angle of View (HOR)°	19.9
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	18.0
Rear (φmm)	13.0
Front Filter Thread (φMxP=)	27.0 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ29 × 36.37
Weight (g)	60



- FIX
- MANUAL
- 5MP
- FA




MODEL NO.	M3520-MPW2
Format (")	2/3
Mount	C
Focal Length (mm)	35
Aperture (F)	2.0-22
Angle of View (HOR)°	14.3
M.O.D. (m)	0.2
Effective Aperture Front (φmm)	18.0
Rear (φmm)	12.0
Front Filter Thread (φMxP=)	27.0 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ29 × 37.34
Weight (g)	59



- FIX
- MANUAL
- 5MP
- FA




MODEL NO.	M5028-MPW2
Format (")	2/3
Mount	C
Focal Length (mm)	50
Aperture (F)	2.8-32
Angle of View (HOR)°	10.0
M.O.D. (m)	0.4
Effective Aperture Front (φmm)	18.0
Rear (φmm)	12.0
Front Filter Thread (φMxP=)	27.0 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ29 × 45.36
Weight (g)	69



- FIX
- MANUAL
- 5MP
- SECURITY
- FA
- FLOATING




MODEL NO.	M2518-MPW
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.8-16
Angle of View (HOR)°	20.5
M.O.D. (m)	0.15
Effective Aperture Front (φmm)	18.0
Rear (φmm)	13.0
Front Filter Thread (φMxP=)	30.5 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ35 × 48.90
Weight (g)	102



- ZOOM
- MANUAL
- FA



MODEL NO.	MLH-10X
Format (")	1/2
Mount	C
Focal Length (mm)	* 0.084-0.84X
Aperture (F)	5.6-32C
Angle of View (HOR)°	18.0-3.6
M.O.D. (m)	0.1524 (6")
Effective Aperture Front (φmm)	30.0
Rear (φmm)	6.4
Front Filter Thread (φMxP=)	46.0 × 0.75
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ48 × 98.5
Weight (g)	260




NOTE : Macro zoom lens * mark shows maximum magnification

- ZOOM
- MANUAL
- 1MP
- FA



MODEL NO.	MLM-3XMP
Format (")	2/3
Mount	C
Focal Length (mm)	* 0.3-1.0X
Aperture (F)	4.5-22C
Angle of View (HOR)°	11.8-2.78
M.O.D. (m)	0.09
Effective Aperture Front (φmm)	15.5
Rear (φmm)	7.0
Front Filter Thread (φMxP=)	34.0 × 0.5
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ36.5 × 79.5
Weight (g)	150




NOTE : Macro zoom lens * mark shows maximum magnification

- ZOOM
- MANUAL
- 5MP
- FA



型名	TEC-V7X
Format (")	1.1
Mount	C
Focal Length (mm)	* 0.07-0.5X
Aperture (F)	4.3-32
Angle of View (HOR)°	7.05-1.12
M.O.D. (m)	0.182
Effective Aperture Front (φmm)	55.2
Rear (φmm)	14.9
Front Filter Thread (φMxP=)	62.0 × 0.75
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ61 × 152.86
Weight (g)	1400




NOTE : Macro zoom lens with telecentric design * mark shows maximum magnification

- FIX
- MANUAL
- SECURITY
- FA



MODEL NO.	TEC-M55
Format (")	2/3
Mount	C
Focal Length (mm)	55
Aperture (F)	2.8-32C
Angle of View (HOR)°	9.2
M.O.D. (m)	0.14
Effective Aperture Front (φmm)	33.0
Rear (φmm)	13.3
Front Filter Thread (φMxP=)	43.0 × 0.75
Dimensions (φxL) (φxHxD) or (WxHxD)mm	φ53 × 92.9
Weight (g)	320




NOTE : Telecentric lens TEC-M55 has 0.75X and 2X rear adapters as option.

MODEL NO.	M55-0.75X	M55-2.0X
Description	Rear converter 0.75X (Designed for TEC-M55)	Rear converter 2.0X (Designed for TEC-M55)
Application	Attached between lens and camera makes focal length 0.75X	Attached between lens and camera makes focal length 2.0X

FIX
MANUAL
5MP
ITS




MODEL NO.	M0918FIC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	9
Aperture (F)	1.8-16C
Angle of View (HOR)°	52.1
M.O.D. (m)	1
Effective Aperture	Front (φmm) 20.1 Rear (φmm) 12.4
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ47.5 × 45
Weight (g)	-



FIX
MANUAL
5MP
ITS




MODEL NO.	M1218FIC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	12
Aperture (F)	1.8-16C
Angle of View (HOR)°	39.3
M.O.D. (m)	1
Effective Aperture	Front (φmm) 20.0 Rear (φmm) 13.2
Front Filter Thread (φMxP=)	40.2 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ47.5 × 45
Weight (g)	-



FIX
MANUAL
5MP
ITS




MODEL NO.	M1616FIC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	16
Aperture (F)	1.6-16C
Angle of View (HOR)°	30.8
M.O.D. (m)	1
Effective Aperture	Front (φmm) 21.9 Rear (φmm) 11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ47.5 × 45
Weight (g)	-



FIX
MANUAL
5MP
ITS




MODEL NO.	M2514FIC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.4-16C
Angle of View (HOR)°	20.0
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 23.4 Rear (φmm) 14.6
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ47.5 × 37.5
Weight (g)	-



FIX
MANUAL
IR
5MP
ITS




MODEL NO.	M3518FIC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	35
Aperture (F)	1.8-16
Angle of View (HOR)°	13.9
M.O.D. (m)	1
Effective Aperture	Front (φmm) 19.8 Rear (φmm) 12.1
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ46.5 × 53.2
Weight (g)	149.2



FIX
MANUAL
IR
5MP
ITS




MODEL NO.	M5020FIC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	50
Aperture (F)	2.0-16C
Angle of View (HOR)°	9.8
M.O.D. (m)	2
Effective Aperture	Front (φmm) 25.2 Rear (φmm) 11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ46.5 × 53.9
Weight (g)	155



FIX
DC
5MP
ITS




MODEL NO.	MG0918FC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	9
Aperture (F)	1.8-360C
Angle of View (HOR)°	52.1
M.O.D. (m)	1
Effective Aperture	Front (φmm) 20.1 Rear (φmm) 12.4
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ42 × 57.8 × 45
Weight (g)	107



FIX
DC
5MP
ITS




MODEL NO.	MG1218FC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	12
Aperture (F)	1.8-360C
Angle of View (HOR)°	39.3
M.O.D. (m)	1
Effective Aperture	Front (φmm) 20.0 Rear (φmm) 13.2
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ42 × 57.8 × 45
Weight (g)	105.6



FIX
DC
5MP
ITS




MODEL NO.	MG1616FC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	16
Aperture (F)	1.6-360C
Angle of View (HOR)°	30.8
M.O.D. (m)	1
Effective Aperture	Front (φmm) 21.9 Rear (φmm) 11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ42 × 57.8 × 45
Weight (g)	112.6



FIX
DC
5MP
ITS



MODEL NO.	MG2514FC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.4-360C
Angle of View (HOR)°	20.0
M.O.D. (m)	1.5
Effective Aperture	Front (φmm) 23.4 Rear (φmm) 14.6
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxH) (φxHxD) or (WxHxD)mm	φ41.7 × 57.8 × 37.4
Weight (g)	102.2




FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL
VARI-FOCAL AUTO IRIS
PINHOLE
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW

FIX
DC
IR
5MP
ITS



NEW

MODEL NO.	MG3518FC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	35
Aperture (F)	1.8-360C
Angle of View (HOR)°	13.9
M.O.D. (m)	1
Effective Aperture Front (φmm)	19.8
Rear (φmm)	12.1
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 56.8 × 53.2
Weight (g)	125.8




FIX
DC
IR
5MP
ITS



NEW

MODEL NO.	MG5020FC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	50
Aperture (F)	2.0-360C
Angle of View (HOR)°	9.8
M.O.D. (m)	2
Effective Aperture Front (φmm)	25.2
Rear (φmm)	11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 56.8 × 53.9
Weight (g)	131.8




FIX
P-iris
5MP
ITS



NEW

MODEL NO.	MG0918KC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	9
Aperture (F)	1.8-16C
Angle of View (HOR)°	52.1
M.O.D. (m)	1
Effective Aperture Front (φmm)	20.1
Rear (φmm)	12.4
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 57.8 × 45
Weight (g)	105




FIX
P-iris
5MP
ITS



NEW

MODEL NO.	MG1218KC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	12
Aperture (F)	1.8-16C
Angle of View (HOR)°	39.3
M.O.D. (m)	1
Effective Aperture Front (φmm)	20.0
Rear (φmm)	13.2
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 57.8 × 45
Weight (g)	103




FIX
P-iris
5MP
ITS



NEW

MODEL NO.	MG1616KC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	16
Aperture (F)	1.8-16C
Angle of View (HOR)°	30.8
M.O.D. (m)	1
Effective Aperture Front (φmm)	21.9
Rear (φmm)	11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 57.8 × 45
Weight (g)	110




※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

FIX
P-iris
5MP
ITS



NEW

MODEL NO.	MG2514KC-MP
Format (")	2/3
Mount	C
Focal Length (mm)	25
Aperture (F)	1.4-16C
Angle of View (HOR)°	20.0
M.O.D. (m)	1.5
Effective Aperture Front (φmm)	23.4
Rear (φmm)	14.6
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ41.7 × 57.8 × 37.4
Weight (g)	100




※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

FIX
P-iris
IR
5MP
ITS



NEW

MODEL NO.	MG3518KC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	35
Aperture (F)	1.8-16C
Angle of View (HOR)°	13.9
M.O.D. (m)	1
Effective Aperture Front (φmm)	19.8
Rear (φmm)	12.1
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 56.8 × 53.2
Weight (g)	123




※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.

FIX
P-iris
IR
5MP
ITS



NEW

MODEL NO.	MG5020KC-MPIR
Format (")	2/3
Mount	C
Focal Length (mm)	50
Aperture (F)	2.0-16C
Angle of View (HOR)°	9.8
M.O.D. (m)	2
Effective Aperture Front (φmm)	25.2
Rear (φmm)	11.0
Front Filter Thread (φMxP=)	40.5 × 0.5
Dimensions (φxD ₁ (P+HxD) or (WxHxD)mm)	φ42 × 56.8 × 53.9
Weight (g)	129



※ P-iris lenses can only be controlled by specifically designed cameras with P-iris software.



MODEL NO.	EX1.5CS
Description	1.5X Extender for CS-mount
Application	Attached between lens and camera - Makes focal length 1.5X



MODEL NO.	EX1.5C
Description	1.5X Extender for C-mount
Application	Attached between lens and camera - Makes focal length 1.5X



MODEL NO.	EX2CS
Description	2X Extender for CS-mount
Application	Attached between lens and camera - Makes focal length 2X




MODEL NO.	EX2C
Description	2X Extender for C-mount
Application	Attached between lens and camera - Makes focal length 2X

FIX
ATHERMAL
17µm




MODEL NO.	TH17V1311-34
Focal Length (mm)	13
Aperture (F)	1.1
Image Circle (mm)	13.6
Mount (mm)	M34 x 0.5 (Pitch)
Wave Band (µm)	8-12
Angle of View (HOR)° (17µm, 640 x480 sensor)	50.3
Back Focal Length (mm) (Include 1mm Ge Window)	12.44
Material Used	Zinc Sulfide
Dimensions	φ30 × 20.9
Weight (g)	19



FIX
ATHERMAL
17µm




MODEL NO.	TH17V1810-34
Focal Length (mm)	18.8
Aperture (F)	1.0
Image Circle (mm)	13.6
Mount (mm)	M34 x 0.5 (Pitch)
Wave Band (µm)	8-12
Angle of View (HOR)° (17µm, 640 x480 sensor)	32.9
Back Focal Length (mm) (Include 1mm Ge Window)	11.3
Material Used	Zinc Sulfide
Dimensions	φ40 × 20.74
Weight (g)	20




FIX
ATHERMAL
17µm




MODEL NO.	TH17V3511-34
Focal Length (mm)	35
Aperture (F)	1.1
Image Circle (mm)	13.6
Mount (mm)	M34 x 0.5 (Pitch)
Wave Band (µm)	8-12
Angle of View (HOR)° (17µm, 640 x480 sensor)	17.7
Back Focal Length (mm) (Include 1mm Ge Window)	13.2
Material Used	Zinc Sulfide
Dimensions	φ46 × 43.1
Weight (g)	94



MODEL NO.	VM100
Description	Extension Tube Kit 40, 20, 10, 5, 1, 0.5mm
Application	Attached between lens and camera - Reduces minimum focusing distance



MODEL NO.	VM400
Description	5mm Adapter Ring
Application	Attached between lens and camera - Adapts C-mount lens to CS-mount camera



CABLE DIAGRAMS OF AUTO IRIS LENSES

FCS series (DC DRIVE)

FCS series Auto Iris Lens, equipped with auto iris mechanism by galvanometer and with ND filter, can be used with only cameras containing amplifier. Connector plug is applied to the end of the cable.

AFCS series (VIDEO DRIVE)

AFCS series Auto Iris Lens is equipped with auto iris mechanism by galvanometer, amplifier and ND spot filter.

	FCS(w/o Amplifier)	AFCS(with Amplifier)
Supplied Power	-	DC8V ~16V 35mA max
Input Signal	-	Video Signal (V or Vs)
Iris Accuracy	-	±15% (Video level)
Sensitivity Adjustment	-	0.5V (p-p) ~1.0V (p-p) (Video signal)
Input Impedance	-	High impedance
Transit Time	-	Approx. 2sec
Light Weighting Method	-	Adjustable between Average-Peak (to be set at average at factory)
Operating Temperature	-10°C~+50°C	-10°C~+50°C

Wiring Diagram

Pin No.

1	Brown	Control (-)
2	Red	Control (+)
3	Yellow	Drive (+)
4	Orange	Drive (-)

AFCS


- RED : VCC(+) DC8V-16V
- WHITE : Video Signal (V or Vs)
- BLACK : Vcc(-)

REMOTE FUNCTIONS

1) LEVEL & ALC remotes have been functioned on the following models

T21Z5816AMS-CS2/AMSP-CS2
H10Z0812AMS-2/AMSP-2
H10Z1218AMS-2/AMSP-2

ALC remote




*Vcc represents input voltage.
*The ALC should be set at the full peak position.

2) LEVEL remote (AS OPTION)

T6Z5710AMS-CS/AMSP-CS
T10Z5712AMS-CS/AMSP-CS
T34Z5518AMS-CS/AMSP-CS
T34Z5518AMSR-CS/AMSPR-CS
H6Z0812AMS/AMSP
H16Z7516AMS/AMSP (-IR)
H16Z7516AMSR/AMSPR (-IR)

LEVEL remote




*Vcc represents input voltage.

3) Override manual

T34Z5518AMSR-CS/AMSPR-CS
H16Z7516AMSR/AMSPR (-IR)
H30Z1015AMSR/AMSPR

Override manual




*Vcc represents input voltage.
*The remote voltage should be set between 1.5 ~ 5.5V, and level remote should be OFF.

WIRING DIAGRAMS FOR MOTORIZED ZOOM LENSES 1

Motorized zoom / 3 motor type

Iris, focus & zoom can be adjusted by controller.




Remarks : Connect together with iris, focus and zoom for common system when necessary.

Motorized zoom / auto iris type


Auto-iris, focus & zoom can be adjusted by controller.

(Some lenses have Level & ALC remote. Please see remote functions at the left page.)

DC Drive



VIDEO Drive




Remarks : Connect together with iris, focus and zoom for common system when necessary.

WIRING DIAGRAMS FOR MOTORIZED ZOOM LENSES 2

Motorized zoom preset potentiometer for focus & zoom

This preset function has been developed for high requirement to automation in CCTV system using potentiometers as position sensor for focusing & zooming.

(Some lenses have Level, ALC & Override remote. Please see remote functions at the left page.)




Remarks : Connect together with iris, focus and zoom for common system when necessary.

Note : Regarding the wiring diagram of x60 and x20 Zoomlens, please refer to the instruction manual.


CAMERA FORMAT

The size of camera's imaging device also affects the angle of view, with the smaller devices creating narrower angles of view when used on the same lens. The format of the lens, however is irrelevant to the angle of view, it merely needs to project an image which will cover the device, i.e.; the same format of the camera or larger. This also means that 1/3" cameras can utilize the entire range of lenses from 1/3" to 2/3", with a 1/3" 8mm lens giving the same angle as a 2/3" 8mm lens. The latter combination also provides increased resolution and picture quality as only the centre of the lens is being utilized, where the optics can be ground more accurately.



FOCAL LENGTH

The focal length of the lens is measured in mm and directly relates to the angle of view that will be achieved. Short focal length provides wide angle of view and long focal length becomes telephoto, with narrow angle of view. A normal angle of view is similar to what we see with our own eye and has a relative focal length equal to the pick up device. The "computer" range calculator is simple device to use for estimating focal length, object dimension and angle of view, alternatively the VM300 view finder gives an optical way of finding focal length.



ANGLE OF VIEW

It is important to know the angle of view of the lens to take in the object. Angle of view changes with focal length of lens and image size of camera. The focal length to cover the object can be calculated from the next formula.


Formula for calculation

$$f = v \times \frac{D}{V} \dots (1) \quad f = h \times \frac{D}{H} \dots (2)$$

- f : focal length of lens
- V : Vertical size of object
- H : Horizontal size of object
- D : Distance from lens to object
- v : vertical size of image (see the following table)
- h : horizontal size of image (see the following table)

FORMAT	2/3 inch	1/2 inch	1/3 inch	1/4 inch
v	6.6mm	4.8mm	3.6mm	2.7mm
h	8.8mm	6.4mm	4.8mm	3.6mm

For example



- (1) In case of vertical size
1/2 inch camera
Vertical size of object
Distance from lens to object
substitute these datas to formula (1)
$$f = 4.8 \times \frac{2500}{330} \approx 36\text{mm}$$
- (2) In case of horizontal size
1/2 inch camera
Horizontal size of object
Distance from lens to object
substitute these datas to formula (2)
$$f = 6.4 \times \frac{2500}{440} \approx 36\text{mm}$$


COMPARISON OF MONITORING IMAGES

※ Images on 1/3" camera

Object distance	2m	5m	10m	20m
Focal length				
f=2.8mm				
f=3.5mm				
f=8mm				
f=30mm				
f=50mm				

DEPTH OF FIELD

The depth of field refers to the area within the field of view which is in focus. A large depth of field means that a large percentage of the field of view is in focus. A small depth of field has only a small section of the field of view in focus. The depth of field is influenced by several factors; a wide angle lens generally has a larger depth of field than a telephoto lens, a higher F stop setting also has a larger depth of field, and high resolution cameras have a larger depth of field.



LENS SPEED AND DEPTH OF FIELD IMAGE

AUTO OR MANUAL IRIS

Generally we tend to use auto iris lenses externally where there are variations in the lighting levels, manual iris lenses are normally for internal applications where the light level remains constant. With the introduction of electronic iris cameras it is now possible to use manual iris lenses in varying light conditions and the camera will electronically compensate, however there are several considerations to this option; the setting of the F stop becomes critical, if the iris is opened fully to allow the camera to work at night, the depth of field will be very small and it may be more difficult to achieve sharp focus even during the day, the camera can maintain normal video levels but it cannot affect the depth of field. If the iris is closed to increase the dept of field the low light performance of the camera will now be reduced.

VIDEO DRIVE OR DC DRIVE


With auto iris lenses it is necessary to control the operation of the iris to maintain perfect picture levels, Video drive lenses contain amplifier circuit to convert the video signal from the camera into iris motor control. With DC drive lenses the camera must contain amplifier circuitry, the lens now only contains the galvanometric iris motor making it less expensive. The deciding factor depends on the auto iris output of the camera, most now have both types.

F STOP

The lens usually has two measurements of F stop or aperture, the maximum aperture (minimum F stop) when the lens is fully open and minimum aperture (maximum F stop) just before the lens completely closes. The F stop has a number of effects upon the final image; a low minimum F stop will mean the lens can pass more light in dark condition, allowing the camera to produce a better image, and a maximum F stop may be necessary where there is a very high level of light or reflection, this will prevent the camera "whiting out" and maintain constant video level. All auto iris lenses are supplied with Neutral Density filters to increase the maximum F stop. The F stop also directly affects the depth of field.


C OR CS MOUNT

Modern cameras and lenses are generally CS mount, with CS mount cameras both types of lenses can be used but the C mount lens requires a 5mm ring (VM400) to be fitted between the camera and lens to achieve a focused image. With C mount cameras it is not possible to use CS mount lenses as it not physically possible to get the lens close enough to the sensor to achieve a focused image.




	C mount lens	CS mount lens
C mount camera	○	×
CS mount camera	needs 5mm ring	○

FLANGE BACK, BACK FOCAL LENGTH, AND MECHANICAL BACK FOCAL LENGTH



- (A) Flange Back**
Distance between the lens flange and CCD focal plane
- (B) Back Focal Length**
Distance between the surface of the rear lens element and CCD focal plane
- (C) Mechanical Back Focal Length**
Distance between the surface of the lens frame and CCD focal plane


ASPHERICAL LENSES




Spherical lenses have constant refractive indices and are commonly used in almost all CCTV lenses. They are designed in such a way so that light passing through the glass and center of a spherical element should fall on a single point on the image plane, but causing some spherical aberration. This problem is resolved by the aspherical lens technology, enabling more light to pass through the element and to focus right on the same point as on the image plane. Supported by more advanced molding technologies, aspherical lenses eliminate the size constraints and improve the overall optical performance compared with more conventional CCTV lenses.

MECHANISM AND ADVANTAGEOUS EFFECT OF IR LENS

NON IR LENS



IR LENS




Day & Night cameras normally operate in the near-infrared / infrared zones at night, making the image "out of focus" and unsuitable if used with a conventional lens. Computar® has developed IR Lenses that utilize a special optical glass material which minimizes light dispersion. As a result, refocusing is not required when used with infrared lighting. The lens is manufactured with a special ED glass (extra dispersion) which does not widely disperse light of different wavelengths and with "special coating". This combination allows the lens to deliver perfect focus under normal lighting and also under IR illumination by transmitting more light to the infrared region.

Daytime



Nighttime



Non IR lens



※ Monitoring images with Day & Night cameras

MEGAPIXEL




CCD and CMOS image sensors use a series of pixels arranged on a 2 dimensional grid. These pixels convert an optical image to an electronic signal. The number of pixels in an image usually defines the resolution, with more pixels meaning higher resolution. A megapixel is defined as one million pixels and a camera with a megapixel sensor is called a megapixel camera.

MEGAPIXEL LENS FOR MEGAPIXEL CAMERA

To capture the full resolution of a megapixel camera, it is essential to use a high quality megapixel lens. Overall image quality is heavily influenced by the quality of the optical image directed onto the image sensor. Megapixel lenses provide high contrast, brightness and sharpness across the entire image plane. Non-megapixel lenses will not fully display the resolution of megapixel sensors, especially in the corners of the image.

Non-megapixel lens with a megapixel camera

Megapixel lens with a megapixel camera



※ Above pictures and chart are image of lens performance.

P-IRIS LENS

Computar® has launched P-iris (Precise iris) lens series targeted at the network camera market. This series is equipped with a stepping motor for digital iris control instead of a conventional galvanometer. With this



technology, Computar® has created a dedicated network camera lens that can systematically control the iris. Combined with specialized software in the camera, P-iris lenses deliver superior picture quality, enhancing contrast, resolution and depth of field in a wide range of applications, not just to maintain the optimum light level to the image as an existing function.

ENHANCING PICTURE QUALITY

Megapixel cameras with the P-iris system minimize the difference in resolution between the center and corners of the image, enhancing overall picture quality and sharpness by enabling the optimal iris position to be set. Also, P-iris limits the iris position to prevent diffraction when the iris becomes too small in extremely bright situations.

MAXIMIZE DEPTH OF FIELD

Having good depth of field throughout the scene is essential to achieve optimized image quality. Unfortunately, megapixel sensors often have small pixels which can cause a narrow depth of field. P-iris technology will optimize the available depth of field, providing overall sharper images and enhancing foreground and background resolution. The technology is particularly useful in scenes where foreground and background resolution is critical, as in a long corridor.

WIDE RANGE OF BOARD AND CS MOUNT OPTIONS

Various vari-focal board lenses using P-iris technology are available to fit a variety of mini dome and bullet camera housings. Computar® also offers a wide range of P-iris CS mount lenses. Each P-iris CS mount lens has a special 4-pin connector on its cable. To protect the cameras from damage, P-iris connector plugs are designed not to fit regular cameras.

FEATURE INDICATION
MODEL NAME CODING RULE
MANUAL IRIS
AUTO IRIS
VARI-FOCAL MANUAL IRIS
VARI-FOCAL AUTO IRIS
PINHOLE MANUAL ZOOM
MOTORIZED ZOOM
MEGAPIXEL
ACCESSORIES THERMAL
TECHNICAL INFORMATION
ANGLE OF VIEW



ANGLE OF VIEW

ANGLE OF VIEW



MONO FOCAL MANUAL IRIS C-MOUNT / CS-MOUNT P7 ~ 8

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
CS MOUNT	T2314FICS-3	1/3	CS	2.3	1.4-16C	-	-	113.3	86.3
	T2616FICS-4	1/3	CS	2.6	1.6-11C	-	-	99.6	74.9
	T0412FICS-3	1/3	CS	4	1.2-16C	-	-	63.9	49.1
	T0812FICS-3	1/3	CS	8	1.2-16C	-	-	34.7	25.9
	H1214FICS-3	1/2	CS	12	1.4-16C	-	30.4	22.8	17.0
C MOUNT	M8513	2/3	C	8.5	1.3-16C	57.4	42.6	32.2	24.2

MONO FOCAL AUTO IRIS DC DRIVE / VIDEO DRIVE P8 ~ 9

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
DC DRIVE	TG2314FCS-3	1/3	CS	2.3	1.4-360C	-	-	113.3	86.3
	TG2616FCS-4	1/3	CS	2.6	1.6-360C	-	-	99.6	74.9
	TG0412FCS-3	1/3	CS	4	1.2-360C	-	-	63.9	49.1
	TG0812FCS-3	1/3	CS	8	1.2-360C	-	-	34.7	25.9
	HG1214FCS-3	1/2	CS	12	1.4-360C	-	30.4	22.8	17.0
	VIDEO DRIVE	TG2314AFCS-3	1/3	CS	2.3	1.4-360C	-	-	113.3
TG2616AFCS-4		1/3	CS	2.6	1.6-360C	-	-	99.6	74.9
HG1214AFCS-3		1/2	CS	12	1.4-360C	-	30.4	22.8	17.0

VARI-FOCAL MANUAL IRIS P10 ~ 12

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
MANUAL IRIS	T2Z1816CS	1/3	CS	1.8-3.6	1.6-16C	-	-	144.2-79.4	109.5-59.6
	T3Z2910CS	1/3	CS	2.9-8.2	1.0-16C	-	-	98.3-35.2	70.7-26.3
	T3Z2910CS-IR	1/3	CS	2.9-8.2	1.0-16C	-	-	95.0-35.6	69.0-26.7
	T3Z3510CS	1/3	CS	3.5-10.5	1.0-16C	-	-	81.6-27.2	59.4-20.4
	T3Z3510CS-IR	1/3	CS	3.5-10.5	1.0-16C	-	-	81.8-27.2	59.2-20.4
	T4Z2813CS-IR	1/3	CS	2.8-12	1.3-16C	-	-	102.2-23.7	74.2-17.8
	T10Z0513CS-3	1/3	CS	5-50	1.3-16C	-	-	51.8-5.6	39.2-4.3
	T5Z8513CS-IR	1/3	CS	8.5-40	1.3-16C	-	-	33.5-7.1	24.4-5.3
	H2Z4516CS-2	1/2	CS	4.5-10	1.6-16C	-	81.3-38.2	60.4-28.7	33.6-16.1
	H3Z4512CS-IR	1/2	CS	4.5-12.5	1.2-16C	-	83.7-30.1	61.3-22.6	45.3-17.0
	H3Z1014CS	1/2	CS	10-30	1.4-16C	-	35.8-12.5	26.8-9.4	20.1-7.0

VARI-FOCAL AUTO IRIS DC DRIVE / VIDEO DRIVE P13 ~ 18

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
DC DRIVE	TG2Z1816FCS	1/3	CS	1.8-3.6	1.6-360C	-	-	144.2-79.4	109.5-59.6
	TG3Z2312FCS	1/3	CS	2.3-6	1.2-360	-	-	114.8-48.2	86.0-36.1
	TG3Z2910FCS	1/3	CS	2.9-8.2	1.0-360C	-	-	98.3-35.2	70.7-26.3
	TG3Z2910FCS-IR	1/3	CS	2.9-8.2	1.0-360C	-	-	95.0-35.6	69.0-26.7
	TG3Z3510FCS	1/3	CS	3.5-10.5	1.0-360	-	-	81.6-27.2	59.4-20.4
	TG3Z3510FCS-IR	1/3	CS	3.5-10.5	1.0-360	-	-	81.8-27.2	59.2-20.4
	TG4Z2813FCS-IR	1/3	CS	2.8-12	1.3-360	-	-	102.2-23.7	74.2-17.8
	TG10Z0513FCS-3	1/3	CS	5-50	1.3-360C	-	-	51.8-5.6	39.2-4.3
	TG5Z8513FCS-IR	1/3	CS	8.5-40	1.3-360C	-	-	33.5-7.1	24.4-5.3
	HG2Z4516FCS-2	1/2	CS	4.5-10	1.6-360C	-	81.3-38.2	60.4-28.7	33.6-16.1
	HG3Z4512FCS-IR	1/2	CS	4.5-12.5	1.2-360	-	83.7-30.1	61.3-22.6	45.3-17.0
	HG3Z1014FCS	1/2	CS	10-30	1.4-360C	-	35.8-12.5	26.8-9.4	20.1-7.0
	VIDEO DRIVE	TG2Z1816AFCS	1/3	CS	1.8-3.6	1.6-360C	-	-	144.2-79.4
TG3Z2910AFCS		1/3	CS	2.9-8.2	1.0-360C	-	-	98.3-35.2	70.7-26.3
TG3Z2910AFCS-IR		1/3	CS	2.9-8.2	1.0-360C	-	-	95.0-35.6	69.0-26.7
TG3Z3510AFCS		1/3	CS	3.5-10.5	1.0-360	-	-	81.6-27.2	59.4-20.4
TG3Z3510AFCS-IR		1/3	CS	3.5-10.5	1.0-360	-	-	81.8-27.2	59.2-20.4
TG4Z2813AFCS-IR		1/3	CS	2.8-12	1.3-36	-	-	102.2-23.7	74.2-17.8
TG10Z0513AFCS-3		1/3	CS	5-50	1.3-360C	-	-	51.8-5.6	39.2-4.3
TG5Z8513AFCS-IR		1/3	CS	8.5-40	1.3-360C	-	-	33.5-7.1	24.4-5.3
HG2Z4516AFCS-2		1/2	CS	4.5-10	1.6-360C	-	81.3-38.2	60.4-28.7	33.6-16.1
HG3Z4512AFCS-IR		1/2	CS	4.5-12.5	1.2-360	-	83.7-30.1	61.3-22.6	45.3-17.0
HG3Z1014AFCS		1/2	CS	10-30	1.4-360C	-	35.8-12.5	26.8-9.4	20.1-7.0

MANUAL ZOOM MANUAL IRIS P19

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
MANUAL IRIS	H6Z0812	1/2	C	8-48	1.2-16C	-	44.6-8.0	33.5-6.1	25.2-4.6
	M6Z1212-3S	2/3	C	12.5-75	1.2-16C	38.3-6.7	28.3-5.0	21.3-3.8	16.0-2.8

MANUAL ZOOM WITH AUTO IRIS DC DRIVE/VIDEO DRIVE P20

	Model No.	Format inch	Mount	Focal Length (mm)	Aperture (F)	Angle of View (HORIZONTAL) UNIT: (°)			
						2/3" (8.8x6.6mm)	1/2" (6.4x4.8mm)	1/3" (4.8x3.6mm)	1/4" (3.6x2.7mm)
DC DRIVE	T6Z5710AIDC-CS	1/3	CS	5.7-34.2	1.0-360C	-	-	45.9-8.1	34.8-6.2
	H6Z0812AIDC	1/2	C	8-48	1.2-560C	-	44.6-8.0	33.5-6.1	25.2-4.6
VIDEO DRIVE	T6Z5710AIVD-CS	1/3	CS	5.7-34.2	1.0-360C	-	-	45.9-8.1	34.8-6.2
	H6Z0812AIVD	1/2	C	8-48	1.2-560C	-	44.6-8.0	33.5-6.1	25.2-4.6

America

CBC (AMERICA) CORP.

New York

55 Mall Drive,
Commack, NY 11725, U.S.A.
Tel : +1 800 422 6707
Fax : +1 631 543 5426
<http://www.computar.com>
computar@cbcamerica.com

CBC (AMERICA) CORP.

Los Angeles Division

21241 South Western Avenue, Suite #160
Torrance, CA 90501, U.S.A.
Tel : +1 877 407 9555
Fax : +1 310 787 0464
<http://www.computar.com>
computar@cbcamerica.com

CBC (AMERICA) CORP.

Mexico Branch Office

Galileo No. 20 - 101, Col. Polanco,
Miguel Hidalgo, 11500, Mexico DF
Tel : +52 55 5280 4660
Fax : +52 55 5280 3073
<http://www.computar.com>
computar@cbcamerica.com

Europe

CBC (EUROPE) GmbH UK Branch London

Unit 9, Garrick Road Industrial Estate
Irving Way, London NW9 6AQ, U.K.
Tel : +44 (0)20 8732 3300
Fax : +44 (0)20 8202 3387
<http://www.cbceurope.com>
info@cbcuk.com

CBC (EUROPE) S.r.l. Milan

Via E. Majorana, 2
20834-Nova Milanese(MB), ITALY
Tel : +39 0362 365079
Fax : +39 0362 40012
<http://www.computar.it>
sales@cbceurope.it

CBC (EUROPE) GmbH Düsseldorf

Hansaallee 191
D-40549 Düsseldorf, GERMANY
Tel : +49 (0)211 53067 0
Fax : +49 (0)211 53067 180
<http://www.cbc-europe.com>
info@cbc-europe.com

CBC (Poland) Sp.z o.o. Warszawa

ul. Anny German 15,
01-794 Warsaw, POLAND
Tel : +48 22 633 90 90
Fax : +48 22 633 90 60
<http://www.cbcpoland.pl>
info@cbcpoland.pl

CBC Co., Ltd. MOSCOW REP OFFICE Moscow

Office 503B, Entrance#3, World Trade Center, 12
Krasnopresnenskaya nab., Moscow,
123610, RUSSIA
Tel : +7 495 258 2161
Fax : +7 495 258 2160
<http://www.cbc.ru>
info@cbc.ru

China

CBC(Beijing) Trading CO.,LTD. Beijing

Room B905-A, Tian Yuan Gang Center,
No.C2 Dong San Huan Bei-Lu,
Chaoyang District,
Beijing, CHINA
Tel : +86 10 6410 8081 Fax : +86 10 6410 8085
<http://www.cbc-china.cn/10/>
kadoi@bjcbc.com.cn

CBC (SHANGHAI) Trading CO., Ltd. Shanghai

Room 1801, GIFIC, No.1438 HongQiao Road,
Changning District, Shanghai, CHINA
Tel : +86 21 3209 2626
Fax : +86 21 3209 2814
<http://www.cbc-china.cn/>
support@cbcsh.com.cn

CBC (GUANGZHOU) Trading CO., Ltd. Guangzhou

Room 1207, CITIC Plaza, No.233 Tian He North
Road, Guangzhou City, Guangdong Province,
CHINA
Tel : +86 20 8752 0039
Fax : +86 20 8752 0131
<http://www.cbc-china.cn/>
xuyong@gzcbc.com.cn

CBC (H.K.) CO., LTD. Hong Kong

Unit 2101, 21/F., Tower 6,
China Hong Kong City, 33 Canton Road,
Tsim Sha Tsui, Kowloon, Hong Kong, CHINA
Tel : +852 2345 8686
Fax : +852 2342 2908
<http://www.cbc-china.cn/>
larrywong@cbc.com.hk

Asia

CBC. S PTE LTD. Singapore

15 Jalan Kilang Barat, #04-03
Frontech Centre, SINGAPORE 159357
Tel : +65 6275 1221
Fax : +65 6275 0766
<http://www.cbcsingapore.com/>
enquiries@cbcs.com.sg

CBC (Thailand) Co.,Ltd. Bangkok

23rd Floor, ITF Tower 140/48,
Silom Road, Suriyawong,
Bangrak, Bangkok 10500
THAILAND
Tel : +66 2231 6506
Fax : +66 2231 6180
<http://www.cbcthailand.com/>

CBC Corporation (India) Private Limited Mumbai

2F B Wing, Marwah Centre,
Krishanlal Marwah Marg,
Andheri East, Mumbai 400 072, INDIA
Tel : +91 22 2857 9798
Fax : +91 22 6649 1708
enquiry@cbcindia.jp

PT. CBC PRIMA Jakarta

MidPlaza II Building, 12th Floor,
Jl.Jend.Sudirman Kav. 10-11
Jakarta Pusat, 10220, INDONESIA
Tel : +62 21 570 7590
Fax : +62 21 570 7591

T-CBC (TAIWAN) CO., Ltd. Taiwan

Room D, 10th Floor, No.365 Fushing N. Rd.,
Taipei, 10543, TAIWAN, R. O. C.
Tel : +886 2 6600 8001
Fax : +886 2 6600 5211
<http://www.t-cbc.com.tw/>
cbc@t-cbc.com.tw



Head Quarters

Image & Information Technology Division
2-15-13, Tsukishima, Chuo-ku,
Tokyo 104-0052, Japan
Tel : +81 (0)3 3536 4837 Fax : +81 (0)3 3536 4771
<http://www.cbc.co.jp>

www.cbc.co.jp
www.computar-global.com

Tokyo HQ Registered



Tokyo HQ Registered

