

- CC-8926TIR** 1/3"Color High Resolution Vari-Focal Infrared Camera
- CC-28926TIR** 1/3"Color Ex-View High Resolution Vari-Focal Infrared Camera
- CC-8726TIR** 1/3"Color High Resolution Vari-Focal Infrared Camera
- CC-8626TIR** 1/3"Color Vari-Focal Infrared Camera
- CC-8826TIR** 1/3"Color Vari-Focal Infrared Camera

### Features

- \* Outdoor installation
- \* 12 LEDs
- \* Radiant distance 30 meters(at least)
- \* Built-in Auto Iris Vari-Focal Lens
- \* 480 TV Line
- \* 1/3" Sony Ex-View CCD
- \* IR Cut Filter Removal Operation, brings true color in daytime and brings excellent low-light sensitive picture under dark environment.
- \* Built in Auto Iris Vari-Focal Lens.
- \* Line Lock available for Sony CCD Camera.
- \* Available IR Distance :10 Meters ( at least ).
- \* Automatic ATW & AWB.
- \* Provide Crisp & Clear picture image both dark and bright area.



## Specifications

Item No.	CC-8926TIR	CC-28926TIR	CC-8726TIR	CC-8626TIR	CC-8826TIR
Description	1/3" High Resolution Vari-Focal IR Camera	1/3" Ex-View Vari-Focal IR Camera	1/3" High Resolution Vari-Focal IR Camera	1/3" Color Vari-Focal IR Camera	1/3" Color Vari-Focal IR Camera
Pick up Element	Sony Super-Had CCD Image Sensor	Sony Ex-View CCD Image Sensor	Panasonic D5 CCD Image Sensor	Panasonic D5 CCD Image Sensor	Sony CCD Image Sensor
Number of Pixels	<NTSC>768 (H) × 494 (V) / <PAL>752 (H) × 582 (V)			<NTSC>510 (H) × 492 (V) / <PAL>512 (H) × 582 (V)	
Back Light Compensation	ON-OFF				
Lens	Auto Iris Vari-Focal Lens (DC Drive)				
Infrared LED	Quantity	12			
	Radiant Distance	10 meters			
Auto Electronics Shutter	ON-OFF				
Link Lock	ON		ON-OFF		ON
ALC	Low-High				
ATW	ON		ON-OFF		ON
BLC	ON-OFF				
Sync. Mode	Internal Sync.				
Scanning System	2:1 Interlace				
Resolution	480 TVL			420 TVL	

S/N Ratio	48db				
Gamma	0.45				
Minimum illumination	0.5Lux, F 1.4	0.03Lux, F 1.4	0.5Lux, F 1.4	0.92Lux, F 1.4	
Horizontal Sync. Frequency	<NTSC> 15.750 KHz <PAL> 15.625 KHz				
Video Output	1.0 Vp-p, 75 ohm				
Power Source	DC 12V / AC 24V / 110V / 220V / 240V				
Power Consumption	3.6W				
Operating Temperature	-10 to +60				
Shutter Control	<NTSC> 1/60-1/100,000 sec. / <PAL>1/50-1/100,000sec				
Dimension	127 (L) × 55(H) ×70(W) mm				
Net Weight	<AC Type> 0.45kg				
<b>Ext. Model</b>	CC-8926DIR / Crystal filter is not moveable	CC-28926DIR / Crystal filter is not moveable	CC-8726DIR / Crystal filter is not moveable	CC-8626DIR / Crystal filter is not moveable	CC-8826DIR / Crystal filter is not moveable